

You need an enclosure for indoor non-clean industrial environment.



## Spacial CRN

---

Introduction	44
Characteristics	45
Selection guide	46
Accessories	55
Dimensions	66

## You need an enclosure for indoor non-clean industrial environment.

This range can be configured according to your needs

4 different services available:



Assemble to order



Mounting of standard accessories



Painting



Machining



### Time Lasting

- Industrial welding process.
  - Epoxy-polyester painting.
  - Foamed-in polyurethane gasket.
- All of the above guarantees quality, water and dust tightness for years. Front folded gutter prevents the entry of water, oil or liquids, ensuring IP66 protection



### Sealed

- Glazed tempered glass door and fully water and dust tight, maintaining IP66 and IK08 protection



### Safety

- For people:**
- Two welded M6 x 15 earth studs welded to the back and one M6 x 15 stud on the door
- For your installation:**
- Water and dust tightness IP66
  - Ruggedness IK10 to protect your component from external impact
  - Hidden hinges to prevent the removal of the door



### Practical

- 4 welded M8 x 15 back studs shouldered 10 mm for direct installation of mounting plate



### Smart

- Welded door reinforcement profile allowing the fixing of equipment in models from 500 mm high



### Convenient








- Large embedded cable-entry plate with a neoprene seal, flush with the back of the enclosure
- Direct fixing or using the brackets fixed from outside

See page 522 for details or consult our web site [www.se.com](http://www.se.com)








Characteristics	Spacial CRN	Spacial CRNG
	39 dimensions for this metal monobloc. Back piece joined to the sides using a special profile forming a protected sealed area.	<ul style="list-style-type: none"> <li>• 17 dimensions with three-point locking system for this metal construction suite of enclosures</li> <li>• All Spacial CRNG models include a three-point locking system</li> </ul>
<b>Material</b>	Steel	
<b>Finish</b>	Structured finish, epoxy-polyester powder	
<b>Colour</b>	RAL 7035 grey	
<b>Ingress protection rating</b>	<ul style="list-style-type: none"> <li>• IP66 for one-door enclosures</li> <li>• IP55 for two-door enclosures according to IEC 60529</li> </ul>	
<b>Mechanical protection rating</b>	IK10 for plain door and IK08 for glazed door according to IEC 62262	
<b>Standards</b>	IEC 62208	
<b>Certifications</b>	<ul style="list-style-type: none"> <li>• UL, CUL</li> <li>• NEMA 4 for single-door enclosure according to UL508A</li> <li>• NEMA 12, 12K and 13 for double-door enclosure according to UL508A</li> <li>• RoHS compliance</li> </ul>	
<b>Installation</b>	<ul style="list-style-type: none"> <li>• Given their strength, metal enclosures are particularly well suited to indoor areas where they may experience impacts</li> </ul>	
<b>Supply</b>	<p><b>Body</b></p> <ul style="list-style-type: none"> <li>• 4 holes for direct fixing</li> <li>• Wall-fixing drill holes sealed with plastic plugs to ensure the degree of protection (supplied as standard)</li> <li>• Wall-fixing bracket fixed from outside (brackets to be ordered separately)</li> <li>• Direct cable entry</li> <li>• Built-in cable-entry plate, flush with the back of the enclosure (without foamed-in gasket to facilitate machining)</li> <li>• Insulated cable entries with knock-outs, available as an accessory</li> <li>• Easy to equip with 4 welded back studs shouldered 10 mm</li> </ul> <p><b>Door</b></p> <ul style="list-style-type: none"> <li>• 3-mm standard double-bar lock as standard. (Wide choice of inserts as accessories)</li> <li>• Foamed-in polyurethane gasket on the doors to guarantee water and dust tightness</li> <li>• Easily reversible door, fixed with two or three invisible metal hinges allowing the door to open to 120°</li> <li>• Reinforcement on plain doors with welded perforated door profiles for equipment fixing from models NSYCRN54150</li> <li>• Welded earth studs on door and body</li> <li>• Delivered with a reusable packaging and technical instructions</li> </ul>	<p><b>Body</b></p> <ul style="list-style-type: none"> <li>• 4 holes for direct fixing</li> <li>• Wall-fixing drill holes sealed with plastic plugs to ensure water and dust tightness (supplied as standard)</li> <li>• Wall-fixing bracket fixed from outside, specific for large dimensions (to be ordered separately).</li> <li>• Built-in cable-entry plate, flush with the back of the enclosure (without foamed-in gasket to facilitate machining)</li> <li>• Easy to equip with 4 welded back studs shouldered 10 mm (6 for widths of 1000 mm and 1200 mm)</li> </ul> <p><b>Door</b></p> <ul style="list-style-type: none"> <li>• Three-point locking system for one and two doors. Standard 5-mm double-bar lock</li> <li>• Door-centring piece on two-door enclosures to ensure proper door alignment</li> <li>• Foamed-in polyurethane gasket on the doors to guarantee water and dust tightness</li> <li>• Reinforcement on plain doors with welded perforated door profiles for equipment fixing</li> <li>• Delivered with a reusable packaging and technical instructions</li> <li>• Easily reversible door, fixed with two or three invisible metal hinges allowing the door to open to 120°</li> <li>• Welded earth studs on door and body</li> </ul>

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Dimensions						Enclosures			Mounting plates				
Height (A) (mm)	Width (B) (mm)	Depth (C) (mm)	Doors	IP	Weight (kg) <sup>(1)</sup>								
						with plain door, with mounting plate	with plain door, without mounting plate	with glazed door, with mounting plate	Plain	Silkscreened	Micro-perforated	Telequick	
200	200	150	1	66	2.5	-	NSYCRN22150 <sup>(2)</sup>	-	NSYMM22	-	-	-	
200	300	150	1	66	3.9	-	NSYCRN23150 <sup>(2)</sup>	-	NSYMM32	-	NSYMF32	-	
250	200	150	1	66	3.2	NSYCRN252150P	NSYCRN252150	-	NSYMM2520	-	-	-	
300	250	150	1	66	4.2	NSYCRN325150P	NSYCRN325150	NSYCRN325150T	NSYMM3025	-	-	NSYMR3025	
300	250	200	1	66	4.9	NSYCRN325200P	NSYCRN325200	NSYCRN325200T	NSYMM3025	-	-	NSYMR3025	
300	300	150	1	66	5.0	NSYCRN33150P	NSYCRN33150	NSYCRN33150T	NSYMM33	-	NSYMF33	NSYMR33	
300	300	200	1	66	6.0	NSYCRN33200P	NSYCRN33200	NSYCRN33200T	NSYMM33	-	NSYMF33	NSYMR33	
300	400	200	1	66	6.4	-	NSYCRN34200	NSYCRN34200T	NSYMM43	NSYMS43	NSYMF43	NSYMR34	
300	450	150	1	66	6.7	-	NSYCRN345150	-	NSYMM3045	-	-	-	
400	300	150	1	66	6.0	NSYCRN43150P	NSYCRN43150	NSYCRN43150T	NSYMM43	NSYMS43	NSYMF43	NSYMR43	
400	300	200	1	66	6.8	NSYCRN43200P	NSYCRN43200	NSYCRN43200T	NSYMM43	NSYMS43	NSYMF43	NSYMR43	
400	400	200	1	66	8.0	NSYCRN44200P	NSYCRN44200	NSYCRN44200T	NSYMM44	NSYMS44	NSYMF44	NSYMR44	
400	600	250	1	66	10.0	NSYCRN46250P	NSYCRN46250	NSYCRN46250T	NSYMM64	NSYMS64	NSYMF64	NSYMR46	
400	600	300	1	66	11.2	-	NSYCRN46300	NSYCRN46300T	NSYMM64	NSYMS64	NSYMF64	NSYMR46	
500	400	150	1	66	8.7	NSYCRN54150P	NSYCRN54150	NSYCRN54150T	NSYMM54	NSYMS54	NSYMF54	NSYMR54	
500	400	200	1	66	9.8	NSYCRN54200P	NSYCRN54200	NSYCRN54200T	NSYMM54	NSYMS54	NSYMF54	NSYMR54	
500	400	250	1	66	11.0	NSYCRN54250P	NSYCRN54250	NSYCRN54250T	NSYMM54	NSYMS54	NSYMF54	NSYMR54	
500	500	250	1	66	12.8	NSYCRN55250P	NSYCRN55250	NSYCRN55250T	NSYMM55	NSYMS55	NSYMF55	NSYMR55	
600	400	150	1	66	9.3	NSYCRN64150P	NSYCRN64150	NSYCRN64150T	NSYMM64	NSYMS64	NSYMF64	NSYMR64	
600	400	200	1	66	10.8	NSYCRN64200P	NSYCRN64200	NSYCRN64200T	NSYMM64	NSYMS64	NSYMF64	NSYMR64	
600	400	250	1	66	12.3	NSYCRN64250P	NSYCRN64250	NSYCRN64250T	NSYMM64	NSYMS64	NSYMF64	NSYMR64	
600	500	150	1	66	11.3	NSYCRN65150P	NSYCRN65150	NSYCRN65150T	NSYMM65	-	NSYMF65	NSYMR65	
600	500	200	1	66	14.3	NSYCRN65200P	NSYCRN65200	NSYCRN65200T	NSYMM65	-	NSYMF65	NSYMR65	
600	500	250	1	66	16.2	NSYCRN65250P	NSYCRN65250	NSYCRN65250T	NSYMM65	-	NSYMF65	NSYMR65	
600	600	200	1	66	16.3	NSYCRN66200P	NSYCRN66200	NSYCRN66200T	NSYMM66	NSYMS66	NSYMF66	NSYMR66	
600	600	250	1	66	18.2	NSYCRN66250P	NSYCRN66250	NSYCRN66250T	NSYMM66	NSYMS66	NSYMF66	NSYMR66	
600	600	300	1	66	19.8	NSYCRN66300P	NSYCRN66300	NSYCRN66300T	NSYMM66	NSYMS66	NSYMF66	NSYMR66	
600	800	300	1	66	26.0	-	NSYCRN68300	NSYCRN68300T	NSYMM86	NSYMS86	NSYMF86	NSYMR68	
700	500	200	1	66	17.3	NSYCRN75200P	NSYCRN75200	NSYCRN75200T	NSYMM75	NSYMS75	NSYMF75	NSYMR75	
700	500	250	1	66	19.3	NSYCRN75250P	NSYCRN75250	NSYCRN75250T	NSYMM75	NSYMS75	NSYMF75	NSYMR75	
800	600	200	1	66	21.8	NSYCRN86200P	NSYCRN86200	NSYCRN86200T	NSYMM86	NSYMS86	NSYMF86	NSYMR86	
800	600	250	1	66	24.8	NSYCRN86250P	NSYCRN86250	NSYCRN86250T	NSYMM86	NSYMS86	NSYMF86	NSYMR86	
800	600	300	1	66	26.3	NSYCRN86300P	NSYCRN86300	NSYCRN86300T	NSYMM86	NSYMS86	NSYMF86	NSYMR86	
800	800	200	1	66	29.5	NSYCRN88200P	NSYCRN88200	NSYCRN88200T	NSYMM88	-	NSYMF88	NSYMR88	
800	800	300	1	66	32.5	NSYCRN88300P	NSYCRN88300	NSYCRN88300T	NSYMM88	-	NSYMF88	NSYMR88	
1000	600	250	1	66	28.4	NSYCRN106250P	NSYCRN106250	NSYCRN106250T	NSYMM106	-	NSYMF106	NSYMR106	
1000	600	300	1	66	30.6	NSYCRN106300P	NSYCRN106300	NSYCRN106300T	NSYMM106	-	NSYMF106	NSYMR106	
1000	800	250	1	66	34.5	NSYCRN108250P	NSYCRN108250	NSYCRN108250T	NSYMM108	-	NSYMF108	NSYMR108	
1000	800	300	1	66	37.4	NSYCRN108300P	NSYCRN108300	NSYCRN108300T	NSYMM108	-	NSYMF108	NSYMR108	

<sup>(1)</sup> Enclosure without mounting plate.

<sup>(2)</sup> Two cable gland plates, one on the top, one on the bottom.

				Cable entries			
							
Bakelite	DIN rail chassis	Aluminium vertical rails <sup>(3)</sup>	Fig.	Type of cable entry	Cable gland plate standard	Cable gland plate insulated	
-	-	-	1	0	NSYTLCRNO	-	
NSYMB32	-	-	1	B	NSYTLCRNB	-	
-	-	-	1	0	NSYTLCRNO	-	
NSYMB3025	-	NSYMDVR3	1	A	NSYTLCRNA	NSYTSACRNA	
NSYMB3025	-	NSYMDVR3	1	A	NSYTLCRNA	NSYTSACRNA	
NSYMB33	NSYMD33	NSYMDVR3	1	B	NSYTLCRNB	NSYTSACRNB	
NSYMB33	NSYMD33	NSYMDVR3	1	B	NSYTLCRNB	NSYTSACRNB	
NSYMB43	-	NSYMDVR3	1	C	NSYTLCRNC	NSYTSACRNC	
NSYMB43	-	NSYMDVR3	1	B	NSYTLCRNB	NSYTSACRNB	
NSYMB43	NSYMD43	NSYMDVR4	1	B	NSYTLCRNB	NSYTSACRNB	
NSYMB43	NSYMD43	NSYMDVR4	1	B	NSYTLCRNB	NSYTSACRNB	
-	-	NSYMDVR4	1	C	NSYTLCRNC	NSYTSACRNC	
NSYMB64	-	NSYMDVR4	1	D	NSYTLCRND	NSYTSACRND	
NSYMB64	-	NSYMDVR4	1	D	NSYTLCRND	NSYTSACRND	
NSYMB54	NSYMD54	NSYMDVR5	2	B	NSYTLCRNB	NSYTSACRNB	
NSYMB54	NSYMD54	NSYMDVR5	2	C	NSYTLCRNC	NSYTSACRNC	
NSYMB54	NSYMD54	NSYMDVR5	2	C	NSYTLCRNC	NSYTSACRNC	
-	-	NSYMDVR5	2	D	NSYTLCRND	NSYTSACRND	
NSYMB64	NSYMD64	NSYMDVR6	2	B	NSYTLCRNB	NSYTSACRNB	
NSYMB64	NSYMD64	NSYMDVR6	2	C	NSYTLCRNC	NSYTSACRNC	
NSYMB64	NSYMD64	NSYMDVR6	2	C	NSYTLCRNC	NSYTSACRNC	
NSYMB65	-	NSYMDVR6	2	B	NSYTLCRNB	NSYTSACRNB	
NSYMB65	-	NSYMDVR6	2	D	NSYTLCRND	NSYTSACRND	
NSYMB65	-	NSYMDVR6	2	D	NSYTLCRND	NSYTSACRND	
-	NSYMD66	NSYMDVR6	2	D	NSYTLCRND	NSYTSACRND	
-	NSYMD66	NSYMDVR6	2	D	NSYTLCRND	NSYTSACRND	
-	NSYMD66	NSYMDVR6	2	D	NSYTLCRND	NSYTSACRND	
-	-	NSYMDVR6	2	E	NSYTLCRNC <sup>(4)</sup>	NSYTSACRNC	
NSYMB75	NSYMD75	NSYMDVR7	2	D	NSYTLCRND	NSYTSACRND	
NSYMB75	NSYMD75	NSYMDVR7	2	D	NSYTLCRND	NSYTSACRND	
NSYMB86	NSYMD86	NSYMDVR8	2	D	NSYTLCRND	NSYTSACRND	
NSYMB86	NSYMD86	NSYMDVR8	2	D	NSYTLCRND	NSYTSACRND	
NSYMB86	NSYMD86	NSYMDVR8	2	D	NSYTLCRND	NSYTSACRND	
-	-	NSYMDVR8	2	E	NSYTLCRNC <sup>(4)</sup>	NSYTSACRNC <sup>(5)</sup>	
-	-	NSYMDVR8	2	E	NSYTLCRNC <sup>(4)</sup>	NSYTSACRNC <sup>(5)</sup>	
NSYMB106	-	NSYMDVR10	2	D	NSYTLCRND	NSYTSACRND	
NSYMB106	-	NSYMDVR10	2	D	NSYTLCRND	NSYTSACRND	
NSYMB108	NSYMD108	NSYMDVR10	2	E	NSYTLCRNC <sup>(4)</sup>	NSYTSACRNC <sup>(5)</sup>	
NSYMB108	NSYMD108	NSYMDVR10	2	E	NSYTLCRNC <sup>(4)</sup>	NSYTSACRNC <sup>(5)</sup>	

<sup>(3)</sup> Order NSYAMCSF, NSYMDVR12 in steel.










<sup>(4)</sup> With two holes.

<sup>(5)</sup> For flange openings type E, two NSYTSACRNC are required.

• For other dimensions, see our application offer.

Dimensions				Electric distribution						
Height (mm)	Width (mm)	Depth (mm)	Doors	DLA insulated Distribution chassis	DL metal distribution chassis	DLM metal distribution chassis	Plain cover plate for DLM	Mounting plate for DLM	Blanking plate	
200	200	150	1	-	-	-	-	-	-	
200	300	150	1	-	-	-	-	-	-	
250	200	150	1	-	-	-	-	-	-	
300	250	150	1	-	NSYDLR18	-	-	-	-	
300	250	200	1	-	NSYDLR18	-	-	-	-	
300	300	150	1	-	-	-	-	-	-	
300	300	200	1	-	-	-	-	-	-	
300	400	200	1	-	-	-	-	-	-	
300	450	150	1	-	-	-	-	-	-	
400	300	150	1	NSYDLA24G	NSYDLR24	NSYDLM24	NSYCTL300DLM	NSYPMP300DLM	NSYATP72G	
400	300	200	1	NSYDLA24G	NSYDLR36	NSYDLM24	NSYCTL300DLM	NSYPMP300DLM	NSYATP72G	
400	400	200	1	-	NSYDLR24 <sup>(1)</sup>	-	-	-	-	
400	600	250	1	-	NSYDLR36 <sup>(1)</sup>	-	-	-	-	
400	600	300	1	-	-	-	-	-	-	
500	400	150	1	NSYDLA48G	-	NSYDLM48	NSYCTL400DLM	NSYPMP400DLM	NSYATP72G	
500	400	200	1	NSYDLA48G	-	NSYDLM48	NSYCTL400DLM	NSYPMP400DLM	NSYATP72G	
500	400	250	1	NSYDLA48G	NSYDLR48	NSYDLM48	NSYCTL400DLM	NSYPMP400DLM	NSYATP72G	
500	500	250	1	-	NSYDLR48 <sup>(1)</sup>	-	-	-	-	
600	400	150	1	NSYDLA48PG	-	NSYDLM48P	NSYCTL400DLM	NSYPMP400DLM	NSYATP72G	
600	400	200	1	NSYDLA48PG	-	NSYDLM48P	NSYCTL400DLM	NSYPMP400DLM	NSYATP72G	
600	400	250	1	NSYDLA48PG	NSYDLR64	NSYDLM48P	NSYCTL400DLM	NSYPMP400DLM	NSYATP72G	
600	500	150	1	-	NSYDLR64	-	-	-	-	
600	500	200	1	-	-	-	-	-	-	
600	500	250	1	-	NSYDLR88	-	-	-	-	
600	600	200	1	-	NSYDLR88	NSYDLM84P	NSYCTL600DLM	NSYPMP600DLM	NSYATP72G	
600	600	250	1	-	-	NSYDLM84P	NSYCTL600DLM	NSYPMP600DLM	NSYATP72G	
600	600	300	1	-	-	NSYDLM84P	NSYCTL600DLM	NSYPMP600DLM	NSYATP72G	
600	800	300	1	-	-	-	-	-	-	
700	500	200	1	NSYDLA66G / NSYDLA88G	-	NSYDLM66 / NSYDLM88	NSYCTL500DLM	NSYPMP500DLM	NSYATP72G	
700	500	250	1	NSYDLA66G / NSYDLA88G	-	NSYDLM66 / NSYDLM88	NSYCTL500DLM	NSYPMP500DLM	NSYATP72G	
800	600	200	1	NSYDLA84G / NSYDLA112G	NSYDLR110	NSYDLM84 / NSYDLM112	NSYCTL600DLM	NSYPMP600DLM	NSYATP72G	
800	600	250	1	NSYDLA84G / NSYDLA112G	-	NSYDLM84 / NSYDLM112	NSYCTL600DLM	NSYPMP600DLM	NSYATP72G	
800	600	300	1	NSYDLA84G / NSYDLA112G	NSYDLR135	NSYDLM84 / NSYDLM112	NSYCTL600DLM	NSYPMP600DLM	NSYATP72G	
800	800	200	1	-	-	-	-	-	-	
800	800	300	1	-	-	-	-	-	-	
1000	600	250	1	-	-	NSYDLM168	NSYCTL600DLM	NSYPMP600DLM	NSYATP72G	
1000	600	300	1	-	-	NSYDLM168	NSYCTL600DLM	NSYPMP600DLM	NSYATP72G	
1000	800	250	1	NSYDLA234G	-	NSYDLM240	NSYCTL800DLM	NSYPMP800DLM	NSYATP72G	
1000	800	300	1	NSYDLA234G	-	NSYDLM240	NSYCTL800DLM	NSYPMP800DLM	NSYATP72G	

Technical changes reserved. Information provided without guarantee. Images are for illustrative purposes only.

Electronic and network		Plinths (100 mm)		Plinths (200 mm)		Installation system		
								
Fixed 19" rack	Swing 19" rack	Single plinths side plate <sup>(1)</sup>	Single plinths front plate <sup>(1)</sup>	Single plinths side plate <sup>(1)</sup>	Single plinths front plate <sup>(1)</sup>	Inner door	Step slides	Wall-fixing lugs
-	-	-	-	-	-	-	-	NSYPFCR
-	-	-	-	-	-	-	-	NSYPFCR
-	-	-	-	-	-	-	-	NSYPFCR
-	-	-	-	-	-	-	-	NSYPFCR
-	-	-	-	-	-	-	NSYSDCR200	NSYPFCR
-	-	-	-	-	-	-	-	NSYPFCR
-	-	-	-	-	-	-	NSYSDCR200	NSYPFCR
-	-	-	-	-	-	-	NSYSDCR200	NSYPFCR
-	-	-	-	-	-	-	-	NSYPFCR
-	-	-	-	-	-	NSYPIN43	-	NSYPFCR
-	-	-	-	-	-	NSYPIN43	NSYSDCR200	NSYPFCR
-	-	-	-	-	-	-	NSYSDCR200	NSYPFCR
NSYVDM8UF	NSYVDM7UP	-	-	-	-	-	NSYSDCR250	NSYPFCR
NSYVDM8UF	NSYVDM7UP	NSYSPS3100SD	NSYSPS3200SD	NSYSPF6100	NSYSPF6200	-	NSYSDCR300	NSYPFCR
-	-	-	-	-	-	NSYPIN54	-	NSYPFCR
-	-	-	-	-	-	NSYPIN54	NSYSDCR200	NSYPFCR
-	-	-	-	-	-	NSYPIN54	NSYSDCR250	NSYPFCR
-	-	-	-	-	-	-	NSYSDCR250	NSYPFCR
-	-	-	-	-	-	NSYPIN64	-	NSYPFCR
-	-	-	-	-	-	NSYPIN64	NSYSDCR200	NSYPFCR
-	-	-	-	-	-	NSYPIN64	NSYSDCR250	NSYPFCR
-	-	-	-	-	-	-	-	NSYPFCR
-	-	-	-	-	-	-	NSYSDCR200	NSYPFCR
-	-	-	-	-	-	-	NSYSDCR250	NSYPFCR
NSYVDM12UF	NSYVDM11UP	-	-	-	-	-	NSYSDCR200	NSYPFCR
NSYVDM12UF	NSYVDM11UP	-	-	-	-	-	NSYSDCR250	NSYPFCR
NSYVDM12UF	NSYVDM11UP	NSYSPS3100SD	NSYSPS3200SD	NSYSPF6100	NSYSPF6200	-	NSYSDCR300	NSYPFCR
-	-	NSYSPS3100SD	NSYSPS3200SD	NSYSPF8100	NSYSPF8200	-	NSYSDCR300	NSYPFCR
-	-	-	-	-	-	NSYPIN75	NSYSDCR200	NSYPFCR
-	-	-	-	-	-	NSYPIN75	NSYSDCR250	NSYPFCR
NSYVDM17UF	-	-	-	-	-	NSYPIN86	NSYSDCR200	NSYPFCR
NSYVDM17UF	NSYVDM16UP	-	-	-	-	NSYPIN86	NSYSDCR250	NSYPFCR
NSYVDM17UF	NSYVDM16UP	NSYSPS3100SD	NSYSPS3200SD	NSYSPF6100	NSYSPF6200	NSYPIN86	NSYSDCR300	NSYPFCR
-	-	-	-	-	-	-	NSYSDCR200	NSYPFCR
-	-	NSYSPS3100SD	NSYSPS3200SD	NSYSPF8100	NSYSPF8200	-	NSYSDCR300	NSYPFCR
NSYVDM21UF	NSYVDM20UP	-	-	-	-	NSYPIN106	NSYSDCR250	NSYPFCR
NSYVDM21UF	NSYVDM20UP	NSYSPS3100SD	NSYSPS3200SD	NSYSPF6100	NSYSPF6200	NSYPIN106	NSYSDCR300	NSYPFCR
-	NSYVDM20U8P	-	-	-	-	NSYPIN108	NSYSDCR250	NSYPFCR
-	NSYVDM20U8P	NSYSPS3100SD	NSYSPS3200SD	NSYSPF8100	NSYSPF8200	NSYPIN108	NSYSDCR300	NSYPFCR

<sup>(1)</sup> To install the plinth to a wall-mounting enclosure, order ref. NSYAPFWM.









Dimensions			Post-fixing	Supporting pole	Canopies	Support bracket	
Height (mm)	Width (mm)	Depth (mm)	Post-fixing device	Supporting pole	Coupling plates	Canopies	Support bracket for enclosure with anti-tilt kit and reinforcement 1400 mm <sup>(2)</sup>
200	200	150	-	-	-	-	NSYCOCNS1400
200	300	150	-	-	-	-	NSYCOCNS1400
250	200	150	-	-	-	NSYTJ2015	NSYCOCNS1400
300	250	150	-	NSYCOCN80	NSYCHCOA	NSYTJ2515	NSYCOCNS1400
300	250	200	-	NSYCOCN80	NSYCHCOA	NSYTJ2520	NSYCOCNS1400
300	300	150	NSYSFPSC30	NSYCOCN80	NSYCHCOB	NSYTJ3015	NSYCOCNS1400
300	300	200	NSYSFPSC30	NSYCOCN80	NSYCHCOB	NSYTJ3020	NSYCOCNS1400
300	400	200	NSYSFPSC40	NSYCOCN80	NSYCHCOC	NSYTJ4020	NSYCOCNS1400
300	450	150	-	-	-	-	NSYCOCNS1400
400	300	150	NSYSFPSC30	NSYCOCN80	NSYCHCOB	NSYTJ3015	NSYCOCNS1400
400	300	200	NSYSFPSC30	NSYCOCN80	NSYCHCOB	NSYTJ3020	NSYCOCNS1400
400	400	200	NSYSFPSC40	NSYCOCN80	NSYCHCOC	NSYTJ4020	NSYCOCNS1400
400	600	250	NSYSFPSC60	NSYCOCN80	NSYCHCOD	NSYTJ6025	NSYCOCNS1400
400	600	300	NSYSFPSC60	NSYCOCN80	NSYCHCOD	NSYTJ6030	NSYCOCNS1400
500	400	150	NSYSFPSC40	NSYCOCN80	NSYCHCOB	NSYTJ4015	NSYCOCNS1400
500	400	200	NSYSFPSC40	NSYCOCN80	NSYCHCOC	NSYTJ4020	NSYCOCNS1400
500	400	250	NSYSFPSC40	NSYCOCN80	NSYCHCOC	NSYTJ4025	NSYCOCNS1400
500	500	250	NSYSFPSC50	NSYCOCN80	NSYCHCOD	NSYTJ5025	NSYCOCNS1400
600	400	150	NSYSFPSC40	NSYCOCN80	NSYCHCOB	NSYTJ4015	NSYCOCNS1400
600	400	200	NSYSFPSC40	NSYCOCN80	NSYCHCOC	NSYTJ4020	NSYCOCNS1400
600	400	250	NSYSFPSC40	NSYCOCN80	NSYCHCOC	NSYTJ4025	NSYCOCNS1400
600	500	150	NSYSFPSC50	NSYCOCN80	NSYCHCOB	NSYTJ5015	NSYCOCNS1400
600	500	200	NSYSFPSC50	NSYCOCN80	NSYCHCOD	NSYTJ5020	NSYCOCNS1400
600	500	250	NSYSFPSC50	NSYCOCN80	NSYCHCOD	NSYTJ5025	NSYCOCNS1400
600	600	200	NSYSFPSC60	NSYCOCN80	NSYCHCOD	NSYTJ6020	NSYCOCNS1400
600	600	250	NSYSFPSC60	NSYCOCN80	NSYCHCOD	NSYTJ6025	NSYCOCNS1400
600	600	300	NSYSFPSC60	NSYCOCN80	NSYCHCOD	NSYTJ6030	NSYCOCNS1400
600	800	300	NSYSFPSC80	-	NSYCHCOC <sup>(1)</sup>	NSYTJ8030	NSYCOCNS1400
700	500	200	NSYSFPSC50	NSYCOCN80	NSYCHCOD	NSYTJ5020	NSYCOCNS1400
700	500	250	NSYSFPSC50	NSYCOCN80	NSYCHCOD	NSYTJ5025	NSYCOCNS1400
800	600	200	NSYSFPSC60	NSYCOCN80	NSYCHCOD	NSYTJ6020	NSYCOCNS1400
800	600	250	NSYSFPSC60	NSYCOCN80	NSYCHCOD	NSYTJ6025	NSYCOCNS1400
800	600	300	NSYSFPSC60	NSYCOCN80	NSYCHCOD	NSYTJ6030	NSYCOCNS1400
800	800	200	NSYSFPSC80	-	NSYCHCOC <sup>(1)</sup>	NSYTJ8020	NSYCOCNS1400
800	800	300	NSYSFPSC80	-	NSYCHCOC <sup>(1)</sup>	NSYTJ8030	NSYCOCNS1400
1000	600	250	-	NSYCOCN80	NSYCHCOD	NSYTJ6025	NSYCOCNS1400
1000	600	300	-	NSYCOCN80	NSYCHCOD	NSYTJ6030	NSYCOCNS1400
1000	800	250	-	-	NSYCHCOC <sup>(1)</sup>	NSYTJ8025	NSYCOCNS1400
1000	800	300	-	-	NSYCHCOC <sup>(1)</sup>	NSYTJ8030	NSYCOCNS1400









<sup>(1)</sup> 2 coupling plates and supporting poles are required.

<sup>(2)</sup> Available in version 1800 mm: Ref. NSYCOCNS1800.

- With three-point locking system
- Ingress protection rating: IP66 for the single-door enclosures and IP55 for the double-door enclosures, according to IEC 60529

- For other dimensions, see our application offer.
- Enclosure without mounting plate..
- In inverted use of silkscreened mounting plates, the marking is inverted.

Dimensions						Enclosures		Mounting plates			
Height (mm)	Width (mm)	Depth (mm)	Doors	IP	Weight (kg)						
						with plain door, without mounting plate	with glazed door, with mounting plate	Plain	Silkscreened	Microperforated	Telequick
800	600	400	1	66	30.0	NSYCRNG86400	NSYCRNG86400T	NSYMM86	NSYMS86	NSYMF86	NSYMR86
800	1000	300	2	55	40.0	NSYCRNG810300D	-	NSYMM108	-	NSYMF108	NSYMR810
800	1200	300	2	55	46.0	NSYCRNG812300D	-	NSYMM128	-	NSYMF128	2x NSYMR86 <sup>(2)</sup>
1000	600	400	1	66	36.0	NSYCRNG106400	NSYCRNG106400T	NSYMM106	-	NSYMF106	NSYMR106
1000	800	400	1	66	43.0	NSYCRNG108400	NSYCRNG108400T	NSYMM108	-	NSYMF108	NSYMR108
1000	1000	300	2 <sup>(1)</sup>	55	47.0	NSYCRNG1010300D	NSYCRNG1010300T	NSYMM1010	-	NSYMF1010	NSYMR1010 <sup>(3)</sup>
1000	1200	300	2	55	55.0	NSYCRNG1012300D	-	NSYMM1210	-	NSYMF1210	NSYMR1012 <sup>(3)</sup>
1000	1200	400	2	55	60.0	NSYCRNG1012400D	-	NSYMM1210	-	NSYMF1210	NSYMR1012 <sup>(3)</sup>
1200	600	300	1	66	37.0	NSYCRNG126300	NSYCRNG126300T	NSYMM126	-	NSYMF126	NSYMR126
1200	600	400	1	66	42.0	NSYCRNG126400	NSYCRNG126400T	NSYMM126	-	NSYMF126	NSYMR126
1200	800	300	1	66	45.0	NSYCRNG128300	NSYCRNG128300T	NSYMM128	-	NSYMF128	NSYMR128
1200	800	400	1	66	50.0	NSYCRNG128400	NSYCRNG128400T	NSYMM128	-	NSYMF128	NSYMR128
1200	1000	300	2	55	56.0	NSYCRNG1210300D	-	NSYMM1210	-	NSYMF1210	NSYMR1210 <sup>(3)</sup>
1200	1000	400	2	55	61.0	NSYCRNG1210400D	-	NSYMM1210	-	NSYMF1210	NSYMR1210 <sup>(3)</sup>
1200	1200	300	2	55	64.0	NSYCRNG1212300D	-	NSYMM1212	-	2x NSYMF126 <sup>(2)</sup>	2x NSYMR126 <sup>(2)</sup>
1200	1200	400	2	55	90.0	NSYCRNG1212400D	-	NSYMM1212	-	2x NSYMF126 <sup>(2)</sup>	2x NSYMR126 <sup>(2)</sup>
1400	1000	300	2	55	80.0	NSYCRNG1410300D	-	NSYMM1410	-	-	NSYMR1410 <sup>(3)</sup>

Dimensions						Cable entries			Cable entries				
Height (mm)	Width (mm)	Depth (mm)	Doors	IP	Weight (kg)								
						Bakelite	DIN rail chassis	Aluminium vertical rails <sup>(4)</sup>	Fig.	Type of cable entry	Cable gland plate standard	Cable gland plate with FL out-out	FlexiCable <sup>(5)</sup>
800	600	400	1	66	30.0	NSYMB86	NSYMD86	NSYMDVR8	3	G	NSYTLG	NSYTLG2FL	NSYTLGME
800	1000	300	2	55	40.0	-	-	NSYMDVR8	4	H	NSYTLE	NSYTLEFL	2x NSYTLEME
800	1200	300	2	55	46.0	-	-	NSYMDVR8	4	H	NSYTLE	NSYTLEFL	2x NSYTLEME
1000	600	400	1	66	36.0	NSYMB106	-	NSYMDVR10	3	G	NSYTLG	NSYTLG2FL	NSYTLGME
1000	800	400	1	66	43.0	NSYMB108	NSYMD108	NSYMDVR10	4	H	NSYTLD	NSYTLDLFL	2x NSYTLDME
1000	1000	300	2 <sup>(1)</sup>	55	47.0	NSYMB1210	-	NSYMDVR10	4	H	NSYTLE	NSYTLEFL	2x NSYTLEME
1000	1200	300	2	55	55.0	NSYMB1210	-	NSYMDVR10	4	H	NSYTLE	NSYTLEFL	2x NSYTLEME
1000	1200	400	2	55	60.0	-	-	NSYMDVR10	4	H	NSYTLE	NSYTLEFL	2x NSYTLEME
1200	600	300	1	66	37.0	-	-	NSYMDVR12	3	G	NSYTLG	NSYTLG2FL	NSYTLGME
1200	600	400	1	66	42.0	-	-	NSYMDVR12	3	G	NSYTLG	NSYTLG2FL	NSYTLGME
1200	800	300	1	66	45.0	-	NSYMD128	NSYMDVR12	4	H	NSYTLD	NSYTLDLFL	2x NSYTLDME
1200	800	400	1	66	50.0	-	NSYMD128	NSYMDVR12	4	H	NSYTLD	NSYTLDLFL	2x NSYTLDME
1200	1000	300	2	55	56.0	NSYMB1210	-	NSYMDVR12	4	H	NSYTLE	NSYTLEFL	2x NSYTLEME
1200	1000	400	2	55	61.0	NSYMB1210	-	NSYMDVR12	4	H	NSYTLE	NSYTLEFL	2x NSYTLEME
1200	1200	300	2	55	64.0	-	-	NSYMDVR12	4	H	NSYTLE	NSYTLEFL	2x NSYTLEME
1200	1200	400	2	55	90.0	-	-	NSYMDVR12	4	H	NSYTLE	NSYTLEFL	2x NSYTLEME
1400	1000	300	2	55	80.0	-	-	-	4	H	NSYTLE	NSYTLEFL	2x NSYTLEME

<sup>(1)</sup> Except glazed door in single door.

<sup>(2)</sup> Order **NSYCRNGSDR** to mount double mounting plate.

<sup>(3)</sup> Ref. **NSYEMR** mandatory.

<sup>(4)</sup> Order **NSYAMCSF**, **NSYMDVR12** in steel.

<sup>(5)</sup> Cable entry FlexiCable IP55