

Wkładki topikowe

Wkładki topikowe o charakterystyce szybkiej - gF, $U_n = 500V$

Prądy znamionowe
20-250 A

Zwarciova zdolność wyłączenia
110 kA

Napięcie znamionowe
400 V, 500 V

NH00/WT-00 gF 500V, 110 kA

I_N (A)	Typ	Nr kodowy	Waga (g)	Pakowanie (szt.)
20	NH00/WT-00 gF 20A/500V	004114341	198	3/90
25	NH00/WT-00 gF 25A/500V	004114333	198	3/90
32	NH00/WT-00 gF 32A/500V	004114334	198	3/90
40	NH00/WT-00 gF 40A/500V	004114335	198	3/90
50	NH00/WT-00 gF 50A/500V	004114336	198	3/90
63	NH00/WT-00 gF 63A/500V	004114337	198	3/90
80	NH00/WT-00 gF 80A/500V	004114338	198	3/90
100	NH00/WT-00 gF 100A/500V	004114339	198	3/90
125	NH00/WT-00 gF 125A/500V	004114340	198	3/90

UWAGA: Wkładki topikowe w wersji górniczej - G posiadają pokrywę korpusu wykonane ze stali.

NH1/WT-1 gF 500V, 110 kA

I_N (A)	Typ	Nr kodowy	Waga (g)	Pakowanie (szt.)
20	NH1/WT-1 gF 20A/500V	004139110	425	3/24
25	NH1/WT-1 gF 25A/500V	004139111	425	3/24
32	NH1/WT-1 gF 32A/500V	004139112	425	3/24
40	NH1/WT-1 gF 40A/500V	004139113	425	3/24
50	NH1/WT-1 gF 50A/500V	004139114	425	3/24
63	NH1/WT-1 gF 63A/500V	004139115	425	3/24
80	NH1/WT-1 gF 80A/500V	004139116	425	3/24
100	NH1/WT-1 gF 100A/500V	004139117	425	3/24
125	NH1/WT-1 gF 125A/500V	004139118	425	3/24
160	NH1/WT-1 gF 160A/500V	004139119	425	3/24
200	NH1/WT-1 gF 200A/500V	004139120	425	3/24
250	NH1/WT-1 gF 250A/500V	004139121	425	3/24

UWAGA: Wkładki topikowe w wersji górniczej - G posiadają pokrywę korpusu wykonane ze stali.

NH2/WT-2C gF 500V, 110 kA

I_N (A)	Typ	Nr kodowy	Waga (g)	Pakowanie (szt.)
20	NH2/WT-2C/gF 20A/500V	004139388	435	3/15
25	NH2/WT-2C/gF 25A/500V	004139389	435	3/15
32	NH2/WT-2C/gF 32A/500V	004139390	435	3/15
40	NH2/WT-2C/gF 40A/500V	004139391	435	3/15
50	NH2/WT-2C/gF 50A/500V	004139392	435	3/15
63	NH2/WT-2C/gF 63A/500V	004139393	435	3/15
80	NH2/WT-2C/gF 80A/500V	004139394	435	3/15
100	NH2/WT-2C/gF 100A/500V	004139395	435	3/15
125	NH2/WT-2C/gF 125A/500V	004139396	435	3/15
160	NH2/WT-2C/gF 160A/500V	004139397	435	3/15
200	NH2/WT-2C/gF 200A/500V	004139398	435	3/15
250	NH2/WT-2C/gF 250A/500V	004139399	435	3/15

NH2/WT2 gF 500V, 100 kA

I_N (A)	Typ	Nr kodowy	Waga (g)	Pakowanie (szt.)
315	NH2/WT2 gF 315A/500V	004139412	586	3/15
355	NH2/WT2 gF 355A/500V	004139413	586	3/15
400	NH2/WT2 gF 400A/500V	004139414	586	3/15

Charakterystyki czasowo-prądowe oraz prądów ograniczonych znajdują się na stronie 736 - 751



NH00/WT-00 gF 125A/500V



NH1/WT-1 gF 250A/500V



NH2/WT-2C gF 250A/500V



NH2/WT-2 gF 355A/500V

Wkładki topikowe o charakterystyce szybkiej - gF, $U_n = 400V$

Prądy znamionowe
20-250 A

Zwarciova zdolność wyłączenia
100 kA

Napięcie znamionowe
400 V



NH00 gF 63A/400V



NH1/WT-1 gF 250A/400V

NH gF 400V, 100 kA

I_N (A)	Typ	Un - 400V						
		Nr kodowy 000 (00C)	Typ	Nr kodowy 00	Typ	Nr kodowy 1C	Typ	Nr kodowy 1
20	NH000 gF 20A/400V	004119200			NH1C gF 20A/400V	004139200		
25	NH000 gF 25A/400V	004119201			NH1C gF 25A/400V	004139201		
32	NH000 gF 32A/400V	004119202			NH1C gF 32A/400V	004139202		
40	NH000 gF 40A/400V	004119203			NH1C gF 20A/400V	004139203		
50	NH000 gF 50A/400V	004119204			NH1C gF 50A/400V	004139204		
63			NH00 gF 63A/400V	004119100	NH1C gF 63A/400V	004139205		
80			NH00 gF 80A/400V	004119101	NH1C gF 80A/400V	004139206		
100			NH00 gF 100A/400V	004119102	NH1C gF 100A/400V	004139207		
125			NH00 gF 125A/400V	004119103	NH1C gF 125A/400V	004139208		
160			NH00 gF 160A/400V	004119104	NH1C gF 160A/400V	004139209		
200							NH1 gF 200A/400V	004139100
250							NH1 gF 250A/400V	004139101

Charakterystyki czasowo-prądowe oraz prądów ograniczonych znajdują się na stronie 736 - 751

Uwaga! Waga i pakowanie wkładek topikowych gF są takie same jak wkładek gG odpowiednich wielkości

Wkładki topikowe o charakterystyce szybkiej - gF, $U_n = 500V$, G - wykonanie górnicze (pokrywy kokpusu wykonane ze stali)



NH00/WT-00 gF 125A/500V G

NH00/WT-00 gF 500V, 110 kA

I_N (A)	Typ	Nr kodowy górnice	Waga (g)	Pakowanie (szt.)
20	NH00/WT-00 gF 20A/500V G	004111141	198	3/90
25	NH00/WT-00 gF 25A/500V G	004111142	198	3/90
32	NH00/WT-00 gF 32A/500V G	004111143	198	3/90
40	NH00/WT-00 gF 40A/500V G	004111144	198	3/90
50	NH00/WT-00 gF 50A/500V G	004111145	198	3/90
63	NH00/WT-00 gF 63A/500V G	004111146	198	3/90
80	NH00/WT-00 gF 80A/500V G	004111147	198	3/90
100	NH00/WT-00 gF 100A/500V G	004111148	198	3/90
125	NH00/WT-00 gF 125A/500V G	004111149	198	3/90

UWAGA: Wkładki topikowe w wersji górniczej - G posiadają pokrywy korpusu wykonane ze stali.



NH1/WT-1 gF 250A/500V G

NH1/WT-1 gF 500V, 110 kA

I_N (A)	Typ	Nr kodowy górnice	Waga (g)	Pakowanie (szt)
20	NH1/WT-1 gF 20A/500V G	004139123	425	3/24
25	NH1/WT-1 gF 25A/500V G	004139124	425	3/24
32	NH1/WT-1 gF 32A/500V G	004139125	425	3/24
40	NH1/WT-1 gF 40A/500V G	004139126	425	3/24
50	NH1/WT-1 gF 50A/500V G	004139127	425	3/24
63	NH1/WT-1 gF 63A/500V G	004139128	425	3/24
80	NH1/WT-1 gF 80A/500V G	004139129	425	3/24
100	NH1/WT-1 gF 100A/500V G	004139130	425	3/24
125	NH1/WT-1 gF 125A/500V G	004139131	425	3/24
160	NH1/WT-1 gF 160A/500V G	004139132	425	3/24
200	NH1/WT-1 gF 200A/500V G	004139133	425	3/24
250	NH1/WT-1 gF 250A/500V G	004139134	425	3/24

UWAGA: Wkładki topikowe w wersji górniczej - G posiadają pokrywy korpusu wykonane ze stali.