

PRODUCT-DETAILS

ACS380-040S-038A-4 ACS380-040S-038A-4, 480VAC, Pn 25HP, I2LD 34A, IP20

General Information	
Global Commercial Alias	ACS380-040S-038A-4
Product ID	3AXD50000322695
ABB Type Designation	ACS380-040S-038A-4
EAN	6438177549871
Catalog Description	ACS380-040S-038A-4, 480VAC, Pn 25HP, I2LD 34A, IP20
Long Description	The ACS380 machinery drive comes in several variants ensuring seamless integration into machines and connecting perfectly to automation systems. It's a great fit for industries such as food and beverage, material handling and textile. Typical applications include mixers, conveyors, EOT and tower cranes, extruders and textile machinery. With the integrated functional safety features, the ACS380 drive can be also part of the machine's safety system via PROFIsafe over PROFINET, ensuring the motor is safely stopped when required. In addition, the drive's software can be easily customized with adaptive programming to match any specific application requirements.

Ordering	
Country of Origin	United States (US) China (CN)
Customs Tariff Number	85352100
Invoice Description	ACS380-040S-038A-4, 480VAC, Pn 25HP, I2LD 34A, IP20
Made To Order	No
Minimum Order Quantity	1 EA
Order Multiple	1 EA
Quote Only	No
Selling Unit of Measure	each

Dimensions	
Product Net Weight	12.787 kg
Product Net Depth / Length	7.126 in
Product Net Height	9.449 in
Product Net Width	10.236 in

Package Level 1 Units	1 E/
Technical	
Frequency (f)	50/60 H
Frame Size	R
Input Voltage (U _{in})	380 480 '
Additional Information	
Product Name	AC Driv
Classifications	
UNSPSC	3912160
Environmental	
WEEE Category	Product Not in WEEE Scop

Categories

 $\mathsf{Drives} \to \mathsf{Low} \; \mathsf{Voltage} \; \mathsf{AC} \; \mathsf{Drives} \to \mathsf{Machinery} \; \mathsf{Drives} \to \mathsf{ACS380} \; \text{-} \; \mathsf{Machinery} \; \mathsf{Drive}$

2