

PRODUCT-DETAILS

ACS580-01-088A-4+B056

ACS580-01-088A-4+B056 PN: 45 kW, IN: 88 A



General Information

Global Commercial Alias	ACS580-01-088A-4+B056
Product ID	3AUA0000083577
ABB Type Designation	ACS580-01-088A-4+B056
EAN	6438177306085
Catalog Description	ACS580-01-088A-4+B056 PN: 45 kW, IN: 88 A

The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.

All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.

Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044086
Invoice Description	ACS580-01-088A-4+B056 PN: 45 kW, IN: 88 A
Made To Order	Yes
Minimum Order Quantity	1 piece

Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	28.3 kg 62.391 lb
Product Net Depth / Length	295 mm 11.614 in
Product Net Height	732 mm 28.819 in
Product Net Width	203 mm 7.992 in
Package Level 1 Depth / Length	835.00 mm 32.874 in
Package Level 1 Height	521.00 mm 20.512 in
Package Level 1 Width	295.00 mm 11.614 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3
Degree of Protection	IP55
Enclosure Type NEMA	Type1
Altitude	1000 m 95
Sound dB (A)	63 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R5
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Heavy-	72 A

Duty Use (I_{HD})	
Output Current, Light-	83 A
Overload Use (I_{LD})	
Output Current, Normal	88 A
Use (I_n)	
Output Power, Heavy-	37 kW
Duty Use (P_{HD})	
Output Power, Light-	45 kW
Overload Use (P_{LD})	
Output Power, Normal	45 kW
Use (P_n)	
Apparent Power Output	61 kV·A
Efficiency Level	IE2
Standby Loss	21 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	294 W	91.9 %	0.5 %
0/50 %	402 W	94.1 %	0.7 %
0/100 %	767 W	94.3 %	1.3 %
50/25 %	325 W	95.5 %	0.5 %
50/50 %	469 W	96.6 %	0.8 %
50/100 %	915 W	96.6 %	1.5 %
90/50 %	545 W	97.8 %	0.9 %
90/100 %	1139 W	97.6 %	1.9 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

Additional Information

Product Main Type	ACS580-01
Product Name	Frequency converter

Classifications

ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Environmental

SCIP	28daf65e-92a8-4810-9f9f-8a94b5b77014 Finland (FI)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-01 - Wall-mounted drive

