

PRODUCT-DETAILS

ACS580-01-293A-4+B056

ACS580-01-293A-4+B056 PN: 160 kW, IN: 293 A



**General Information**

Global Commercial Alias	ACS580-01-293A-4+B056
Product ID	3AUJ0000083583
ABB Type Designation	ACS580-01-293A-4+B056
EAN	6438177306146
Catalog Description	ACS580-01-293A-4+B056 PN: 160 kW, IN: 293 A

The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.

Long Description

All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.

**Ordering**

Country of Origin	Finland (FI)
Customs Tariff Number	85044085
Invoice Description	ACS580-01-293A-4+B056 PN: 160 kW, IN: 293 A
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No

Selling Unit of Measure piece

## Dimensions

Product Net Weight	69 kg 152.119 lb
Product Net Depth / Length	393 mm 15.472 in
Product Net Height	965 mm 37.992 in
Product Net Width	300 mm 11.811 in
Package Level 1 Depth / Length	1145.00 mm 45.079 in
Package Level 1 Height	630.00 mm 24.803 in
Package Level 1 Width	485.00 mm 19.094 in
Package Level 1 Units	1 carton

## Technical

Number of Phases	3
Degree of Protection	IP55
Enclosure Type NEMA	Type1
Altitude	1000 m 95
Sound dB (A)	65 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R8
Input Voltage ( $U_{in}$ )	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Heavy-Duty Use ( $I_{HD}$ )	246 A
Output Current, Light-Overload Use ( $I_{LD}$ )	278 A
Output Current, Normal Use ( $I_n$ )	293 A

Output Power, Heavy-Duty Use ( $P_{HD}$ )	132 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	160 kW
Output Power, Normal Use ( $P_n$ )	160 kW
Apparent Power Output Efficiency Level	203 kV-A IE2
Standby Loss	47 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	981 W	91.8 %	0.5 %
0/50 %	1382 W	93.9 %	0.7 %
0/100 %	2541 W	94.3 %	1.3 %
50/25 %	1088 W	95.5 %	0.5 %
50/50 %	1582 W	96.5 %	0.8 %
50/100 %	3032 W	96.6 %	1.5 %
90/50 %	1907 W	97.7 %	0.9 %
90/100 %	4071 W	97.5 %	2.0 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

## Additional Information

Product Main Type	ACS580-01
Product Name	Frequency converter

## Classifications

ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

## Environmental

SCIP	1b7d3fcb-8dfc-4964-9a9a-bec89b35caf1 Finland (FI)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

## Categories

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-01 - Wall-mounted drive

