

# XY2CE2A470

Latching emergency stop rope pull switch,  
Telemecanique rope pull switches XY2C, e  
XY2CE, LH side -2NC, key release pushbutton



## Main

|                           |   |
|---------------------------|---|
| Range of product          | Telemecanique Emergency stop rope pull switches XY2C                    |
| Product or component type | Latching emergency stop rope pull switch                                |
| Device short name         | XY2CE   |
| Housing colour            | Red RAL 3000  |
| Overtoltage category      | Class I conforming to EN/IEC 61140<br>Class I conforming to NF C 20-030 |

## Complementary

|  |   |
|--|---|
| Local signalling                             | Without pilot light   |
| Number of cables                             | 1   |
| Trigger cable maximum length                 | 70 m  |
| Body material                                | Zamak   |
| Cover material                               | Stainless steel   |
| Reset  | By key-release push-button  |
| Key number                                   | 421   |
| Contacts type and composition                | 2 NC  |
| Contact operation                            | Slow-break  |
| Trigger cable anchor point                   | LH side   |
| Connections - terminals                      | Screw clamp terminal, 1 x 0.5...2 x 1.5 mm <sup>2</sup>   |
| Tightening torque                            | 0.8...1.2 N.m   |
| Cable entry number                           | 3 plain hole for Pg 13.5 or ISO M20 cable gland   |
| Safety level                                 | Can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to EN/IEC 61508 |
| Safety reliability data                      | B10d = 300000 conforming to IEC 60947-5-5 value given for a life time of 20 years limited by mechanical or contact wear   |
| Marking                                      | CE  |
| Mechanical durability                        | 60000 cycles  |
| Distance between cable supports              | 5 m   |
| [Ie] rated operational current               | 3 A at 240 V, AC-15, A300 conforming to EN/IEC 60947-5-1 appendix A<br>0.27 A at 250 V, DC-13, Q300 conforming to EN/IEC 60947-5-1 appendix A   |
| [Ithe] conventional enclosed thermal current | 10 A  |
| [Ui] rated insulation voltage                | 500 V (pollution degree 3) conforming to EN/IEC 60947-1<br>300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14  |
| [Uimp] rated impulse withstand voltage       | 6 kV conforming to EN/IEC 60947-1   |
| Positive opening                             | With conforming to EN/IEC 60947-5-1   |
| Maximum resistance across terminals          | 25 MOhm conforming to EN/IEC 60255-7 category 3<br>25 MOhm conforming to NF C 93-050 method A   |
| Short-circuit protection                     | 10 A cartridge fuse type gG conforming to EN/IEC 60269  |
| Terminals description ISO n°1                | (21-22)NC<br>(11-22)NC  |

|                    |         |
|--------------------|---------|
| Net weight         | 1.47 kg |
| Compatibility code | XY2CE   |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | EN/IEC 60947-5-1<br>Machinery directive 2006/42/EC<br>EN/IEC 60947-5-5<br>Work equipment directive 2009/104/EC<br>UL 508<br>CSA C22.2 No 14<br>EN/IEC 60204-1<br>EN/ISO 13850 |
| Product certifications                | UL category NISD emergency stop devices<br>CSA<br>CCC   |
| Protective treatment                  | TC  |
| Ambient air temperature for operation | -25...70 °C   |
| Ambient air temperature for storage   | -40...70 °C   |
| Vibration resistance                  | 10 gn (f= 10...300 Hz) conforming to EN/IEC 60068-2-6   |
| Shock resistance                      | 50 gn 11 ms conforming to EN/IEC 60068-2-27   |
| IP degree of protection               | IP65 conforming to IEC 60529  |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 8.6 cm   |
| Package 1 Width              | 16.0 cm  |
| Package 1 Length             | 20.0 cm  |
| Package 1 Weight             | 1.6 kg   |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 2        |
| Package 2 Height             | 15.0 cm  |
| Package 2 Width              | 30.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 3.645 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions



- (1) 3 plain holes for Pg 13.5 cable gland.
- (2) Maximum extension.
- Ø 4 elongated holes Ø 6 mm/0.24 in.

Electrical Curves

AC Supply 50/60 Hz Inductive Circuit

2-pole Contact Block



Y Millions of operating cycles  
X Current in A

DC Supply Power Broken in for 1 Million Operating Cycles Inductive Circuit

|           |   |    |    |     |
|-----------|---|----|----|-----|
| Voltage   | V | 24 | 48 | 120 |
| <i>mm</i> | W | 13 | 9  | 7   |