

PRODUCT-DETAILS

MCRC031ATD

MCRC031ATD Mini Contactor Relay 3NO+1NC 24VDC



General Information

Extended Product Type	MCRC031ATD
Product ID	1SAH100016R9900
EAN	4013614547003
Catalog Description	MCRC031ATD Mini Contactor Relay 3NO+1NC 24VDC
Long Description	The MCRC031ATD mini contactor relay is a dimension optimized 4 pole contactor relay with screw terminals. This device is a great solution when high performances are needed but the space is limited. Mini contactors are used in residential buildings, commercial buildings and industrial applications for switching of control signals up to 6 A / 240 V (AC-15). The product is suitable for wall or rail mounting.

Ordering

EAN	4013614547003
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions

Product Net Width	45 mm
Product Net Height	48 mm
Product Net Depth /	68 mm

Length

Product Net Weight	0.235 kg
--------------------	----------

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	46 mm
Package Level 1 Height	70 mm
Package Level 1 Depth / Length	49 mm
Package Level 1 Gross Weight	0.24 kg
Package Level 1 EAN	4013614547003
Package Level 2 Units	box 10 piece
Package Level 2 Width	243 mm
Package Level 2 Height	80 mm
Package Level 2 Depth / Length	106 mm
Package Level 2 Gross Weight	2.46 kg
Package Level 2 EAN	4013614547409

Environmental

Ambient Air Temperature	Operation -40 ... +55 °C Storage -55 ... +80 °C
Maximum Operating Altitude Permissible	3000 m
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 3 ... 150 Hz
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 25g
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Contact Rating UL/CSA	A600 Q600
General Use Rating UL/CSA	(600 V AC) 10 A
Connecting Capacity Auxiliary Circuit UL/CSA	Stranded 1/2x 18-12 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 7 in-lb Control Circuit 7 in-lb Main Circuit 7 in-lb
Pilot Duty of Contact Elements acc. UL508	A600 Q600

Additional Information

Coil Consumption	Average Holding Value DC 3 W Average Pull-in Value DC 3 W
------------------	--

Coil Operating Limits	(acc. to IEC 60947-5-1) for DC supply 0.85 ... 1.1 x U _c (at $\theta \leq 55^\circ\text{C}$)
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1x 0.75 ... 4 mm ² Rigid 2x 0.75 ... 2.5 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Conventional Free-air Thermal Current (I _{th})	Auxiliary Circuit 10 A
Degree of Protection	Auxiliary Circuit Terminals IP20 Control Circuit Terminals IP20 Main Circuit Terminals IP20
Maximum Electrical Switching Frequency	(AC-15) 360 cycles per hour (DC-13) 360 cycles per hour
Mechanical Durability	10000000 cycle
Mini Contactor Type	Mini Contactor Relay
Minimum Switching Capacity	Auxiliary Circuit 17 V Auxiliary Circuit 5 mA
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position	Any, Position 1-6
Mounting Type	DIN-rail Screw
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	3
Number of Poles	0
Number of Main Contacts NC	0
Number of Main Contacts NO	0
Power Loss	at Rated Operating Conditions per Pole 0.4 W
Product Main Type	MCR
Product Name	Mini Contactor Relay
Rated Control Circuit Voltage (U _c)	24 V DC
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Control Circuit DC
Rated Impulse Withstand Voltage (U _{imp})	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U _i)	750 V
Rated Operational Current AC-15 (I _θ)	(240 V) 6 A (400 V) 4 A (500 V) 2.5 A (690 V) 1.5 A
Rated Operational Current	(24 V) 5 A

DC-13 (I _e)	(48 V) 2.5 A (125 V) 0.55 A (250 V) 0.3 A (440 V) 0.15 A
Rated Operational Voltage	Auxiliary Circuit 690 V AC Auxiliary Circuit 440 V DC
Standards	IEC/EN 60947-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-5-1
Terminal Type	Screw Terminals
Tightening Torque	Auxiliary Circuit 0.8 ... 1.0 N·m Control Circuit 0.8 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm Control Circuit 9 mm

Certificates and Declarations (Document Number)

BV Certificate	1SAA971000-0201
CB Certificate	1SAA971001-2001
CQC Certificate	CQC2019010303193580
cULus Certificate	cUL_E48139
Declaration of Conformity - CCC	2020980303000255
Declaration of Conformity - CE	1SAD938502-0305
Instructions and Manuals	2CDC103061M6801
RoHS Information	1SAD038501-0305

Classifications

ETIM 5	EC000196 - Contactor relay
ETIM 6	EC000196 - Contactor relay
ETIM 7	EC000196 - Contactor relay
Object Classification Code	K
UNSPSC	39121500
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.0 : 27371001

Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactor Relays

