

# Product datasheet

Specifications



## Fuse carrier TeSys DF, 3P+N 125A, fuse size 22x58 mm, blown fuse indicator

Local distributor code: 393394339 DF223NVC

EAN Code : 3389118233447

### Main

|  |   |
|--|---|
| Range                                  | TeSys   |
| Product name                           | TeSys DF  |
| Product or component type              | Fuse carrier  |
| Device short name                      | DF22  |
| Device composition                     | tubular link for locked in Neutral pole   |
| Product compatibility                  | DF3FA fuse cartridge striker<br>DF3FN fuse cartridge striker<br>DF22AM auxiliary contact block                            |
| Poles description                      | 3P + N  |
| Fuse size                              | 22 x 58 mm  |
| Fuse type                              | , gG<br>, aM  |
| Control type                           | Toggle  |
| Local signalling                       | Blown fuse indication   |
| [Ue] rated operational voltage         | 690 V AC<br>690 V DC  |
| [Ie] rated operational current         | 125 A   |
| [Ui] rated insulation voltage          | 690 V AC  |
| [Uimp] rated impulse withstand voltage | 8 kV  |
| [Ipk] rated peak withstand current     | 19 kA with tubular links conforming to IEC 60269-1  |
| Short-circuit withstand                | 120 kA 400 V conforming to IEC 60947-3<br>120 kA 500 V conforming to IEC 60947-3<br>80 kA 690 V conforming to IEC 60947-3 |

### Complementary

|                        |  |
|------------------------|--|
| Standards              | EN/IEC 60947-3<br>EN/IEC 60269-2<br>UL 4248-1<br>CSA C22.2 No 4248-1 |
| Product certifications | IEC<br>UL recognized<br>CSA<br>EAC                                   |
| Mounting support       | 35 mm symmetrical DIN rail   |
| Mounting position      | Vertical (tolerance: +/- 23°)  |

|                                |  |
|--------------------------------|--|
| <b>Connections - terminals</b> | Screw clamp terminals 1 cable(s) 2.5...35 mm <sup>2</sup> rigid<br>Screw clamp terminals 2 cable(s) 2.5...25 mm <sup>2</sup> rigid<br>Screw clamp terminals 1 cable(s) 2.5...35 mm <sup>2</sup> flexible with or without<br>Screw clamp terminals 2 cable(s) 2.5...25 mm <sup>2</sup> flexible with or without |
| <b>Tightening torque</b>       | 4 N.m  |
| <b>Height</b>                  | 127.5 mm   |
| <b>Width</b>                   | 140 mm   |
| <b>Depth</b>                   | 76.5 mm  |
| <b>Net weight</b>              | 0.895 kg   |
| <b>Quantity per set</b>        | Set of 1   |

## Environment

|  |                                      |
|--|--------------------------------------|
| <b>Ambient air temperature for storage</b>   | -40...80 °C                          |
| <b>Ambient air temperature for operation</b> | -20...60 °C with derating above 20°C |
| <b>IP degree of protection</b>               | IP20 conforming to IEC 60529         |
| <b>Protective treatment</b>                  | TH                                   |
| <b>Fire resistance</b>                       | 960 °C conforming to IEC 60695-2-1   |
| <b>Compatibility code</b>                    | DF22                                 |

## Packing Units

|                                     |         |
|-------------------------------------|---------|
| <b>Unit Type of Package 1</b>       | PCE     |
| <b>Number of Units in Package 1</b> | 1       |
| <b>Package 1 Height</b>             | 8.4 cm  |
| <b>Package 1 Width</b>              | 22.4 cm |
| <b>Package 1 Length</b>             | 13.2 cm |
| <b>Package 1 Weight</b>             | 840.0 g |
| <b>Unit Type of Package 2</b>       | S03     |
| <b>Number of Units in Package 2</b> | 9       |
| <b>Package 2 Height</b>             | 30.0 cm |
| <b>Package 2 Width</b>              | 30.0 cm |
| <b>Package 2 Length</b>             | 40.0 cm |
| <b>Package 2 Weight</b>             | 7.99 kg |

## Offer Sustainability

|                                   |   |
|-----------------------------------|---|
| <b>Sustainable offer status</b>   | Green Premium product   |
| <b>REACH Regulation</b>           | <a href="#">REACH Declaration</a>   |
| <b>REACH free of SVHC</b>         | Yes   |
| <b>EU RoHS Directive</b>          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| <b>Toxic heavy metal free</b>     | Yes   |
| <b>Mercury free</b>               | Yes   |
| <b>China RoHS Regulation</b>      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |
| <b>RoHS exemption information</b> | Yes   |
| <b>Environmental Disclosure</b>   | <a href="#">Product Environmental Profile</a>   |

---

**WEEE**

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

## **Contractual warranty**

---

**Warranty**

18 months

**Recommended replacement(s)**