

PRODUCT-DETAILS

# OVR T1-T2 4L 12.5-275s P QS

## OVR T1-T2 4L 12.5-275s P QS Surge Protective Device



### General Information

Extended Product Type	OVR T1-T2 4L 12.5-275s P QS
Product ID	2CTB815710R2300
EAN	3660308525017
Catalog Description	OVR T1-T2 4L 12.5-275s P QS Surge Protective Device
Long Description	OVR T1-T2 4L 12.5-275s P QS Surge Protective Device

### Technical

Standards	IEC 61643-11 / EN 61643-11
Type of Low Voltage Distribution System	TN-S
Suitable For	To protect the systems against the transient overvoltage (lightning)
Nominal AC Voltage of the System ( $U_o$ )	230 / 400 V
Voltage Rating DC	350 V
Voltage Protection Level ( $U_p$ )	(L-N) 2.8 kV (N-PE) 1.4 kV (L-PE) 1.4 kV
Maximum Continuous Operating Voltage ( $U_c$ )	(L-PE) 275 V (L-L) 440 V (L-N) 440 V (N-PE) 275 V

Temporary Overvoltage Test Value ( $U_T$ )	337 V
Discharge Current	Nominal 20 kA Maximum 80 kA Total 320 kA
Impulse Current	I (imp, 10 / 350 $\mu$ s) 12.5 kA I (total, 10 / 350 $\mu$ s) 50 kA
Lightning Impulse Current	12,5
Short Circuit Withstand I <sub>cc</sub>	100 kA
Follow Current Extinction Capacity I <sub>f</sub> (I <sub>fi</sub> )	(L-N) - kA (N-PE) - kA
Power Loss	63 mW
Short-Circuit Protective Devices	Curve B Breakers $\leq$ 125 A Curve C Breakers $\leq$ 125 A gL Type Fuses $\leq$ 160 A gG Type Fuses $\leq$ 160 A
Arrester Class	I II
Number of Protected Poles	4
Number of Poles	4
Position of Neutral Terminals	Right
Version	Plug-in
Mounting Type	DIN-Rail
Product Type	QS
Options Provided	Industry, commercial building
Preventive Maintenance Feature	Yes
Status Indicator	Yes
Fuse Size	4 modular spacing

## Environmental

Degree of Protection	IP20
Maximum Operating Altitude Permissible	Without Derating 5000
RoHS Status	Following EU Directive 2011/65/EU
RoHS Information	9AKK108466A4617
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Width in Number of Modular Spacings	4
Product Net Width	71.2 mm
Product Net Height	88 mm
Product Net Depth / Length	76.7 mm
Product Net Weight	0.6 kg

## Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.600 kg
E-Number (Finland)	3217623

---

## Certificates and Declarations

CQC Certificate	9AKK107680A1975
Declaration	2CTC432056G1701
Declaration of Conformity - CE	9AKK108466A4617
EAC Certificate	2CTC436008G1701

---

## Installation

Instructions and Manuals	2CTC431030M1701
--------------------------	-----------------

---

## Popular Downloads

Data Sheet, Technical Information	2CTC431048D0201
Mechanical Drawings	2CTC800015F2100.pdf 2CTC800015F2101.dxf 2CTC800015F2102.stp 2CTC800015F2103.igs

---

## Classifications

ETIM 8	EC001457 - Combined arrester for power supply systems
ETIM 9	EC001457 - Combined arrester for power supply systems
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85363090
eClass	V11.0 : 27130808
Object Classification Code	141BCC

---

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPD Class I → Type T1 - T2 12.5kA

