




# OVR H T2-T3 20-275 P QS

## 2CTB803871R2600

11/03/2016

Type
T2-T3

Imax : 20 kA

Up: < 0,9 kV
System
TT/TNS : 230 V

According to IEC 61643-11

Type 2 SPD's are designed to discharge the currents generated by indirect lightning strikes causing induced or conducted overvoltages on the power distribution network.

They are characterized by an 8/20µs waveform (Imax). Higher is the Imax, more powerful they are.

They are installed in the main distribution switchboard but also in sub-distribution board.

They have a low residual voltage Up often compatible with the withstand voltage of the equipment to protect. If this is not the case or the cable length to the equipment is longer than 10m, another level of coordination with OVR T2-T3, OVR T3 will be needed.

- Din rail mounting
- Common and differential protection mode
- Pro M compact design
- Back up protection up to 125 A Fuse



<b>CHARACTERISTICS</b>	<b>Key characteristics</b>			
	Protection mode			L-N/L-PE/N-PE
	Number of protected lines			1
	Test class			II-III
	Integrated thermal disconnecter			Yes
	End of life indicator			Yes
	Safety reserve			No
	<b>Electrical characteristics</b>			
	Nominal discharge current	$I_n$ (8/20)	kA	5
	Maximal discharge current	$I_{max}$ (8/20)	kA	20
	Impulse current	$I_{imp}$ (10/350)	kA	2
	Maximal continuous operating voltage	$U_c$	V	275
	Type of current / frequency		Hz	a.c. 47-63
	Voltage protection level at In	$U_p$ (L-PE)	kV	0,9
	Voltage protection level at In	$U_p$ (L-N)	kV	-
	Voltage protection level at In	$U_p$ (N-PE)	kV	-
	Short circuit withstand	$I_{SCCR}$	kA	100
	Total current	$I_{TOTAL}$	kA	20
	Follow current interrupted	$I_{fi}$	kA	-/-
	Ground residual current	$I_{PE}$	µA	< 350
	TOV withstand (L-N : 5s / N-PE : 200 ms)	$U_T$	V	337
	Voltage Combination Wave	$U_{oc}$	kV	10
	<b>Required thermal/back up protection</b>			
	Curve B or C Circuit breaker	A		≤ 125
	gG - gL fuse	A		≤ 125
Comments				
<b>Mechanical characteristics</b>				
Dimensions	H x W x D	mm	88 x 17,8 x 58	
Wire range : Solid wire		mm <sup>2</sup>	2.5...25	
Wire range : Stranded wire		mm <sup>2</sup>	2.5...16	
Stripping length		mm	12.5	
Packing quantities		piece	Per 1	
<b>Miscellaneous characteristics</b>				
Maximal altitude	m		2000	
Weight	g		120	
Response time	ns		< 25	
Fire resistance according to UL 94			V-0	
Replacement cartridges				
Phase / Product ID	OVR H T2-T3 20-275 C QS 2CTB803876R1300			
Neutral / Product ID	-			

