Product data sheet Characteristics

ZCKE085

Limit switch head, Limit switches XC Standard, ZCKE, spring rod, +120 °C



Range of produc Series name Standard format Product or component type Device short name ZCKE Head type Multi-directional head Product compatibility XCKJ Associated body ZCKJ7H7 ZCKJD31H7 ZCKJD31H7 ZCKJD37H7 ZCKJD37H7 ZCKJD37H7 ZCKJD35H7 ZCKJD35H7 ZCKJB39 ZCKJ11 ZCKJB39H7 ZCKJB49 ZCKJ11H7 ZCKJB49 ZCKJ11H7 ZCKJB49 ZCKJB48 ZCKJ	Main	
Product or component type Device short name ZCKE Head type Multi-directional head Product compatibility XCKJ Associated body ZCKJ7H7 ZCKJD31H7 ZCKJ2 ZCKJ7H29 ZCKJ9H7 ZCKJ9H7 ZCKJ9H7 ZCKJ9H7 ZCKJ11H7 ZCKJ035H7 ZCKJ11 ZCKJ039H7 ZCKJ11 ZCKJ039H7 ZCKJ11 ZCKJ039H7 ZCKJ11429 ZCKJ1H29 ZCKJ1H29 ZCKJ1H29 ZCKJ11H29 ZCKJ11H29 ZCKJ11H29 ZCKJ2H29 ZCKJ11H29 ZCKJ2H29 ZCKJ11H29 ZCKJ037H29 ZCKJ037H29 ZCKJ037H29 ZCKJ037H29 ZCKJ037H29 ZCKJ031H29 ZCKJ031H29 ZCKJ1H29 ZCKJ1H29 ZCKJ1H29 ZCKJ8 ZCKJ1H29 ZCKJB3H29 ZCKJ2H7 ZCKJ039 ZCKJ2H7 ZCKJ039 ZCKJ031 ZCKJ2H7 ZCKJ035 ZCKJ1H7 ZCKJ1H1 ZCKJ1H1 ZCKJ1H1 ZCKJ1H1 ZCKJ1H1 ZCKJ1H1 ZCKJ1H2 Movement of operating Multi-directional head Type of operator Spring rod spring return	Range of produc	Telemecanique Limit switches XC Standard
type Device short name ZCKE Head type Multi-directional head Product compatibility XCKJ Associated body ZCKJ7H7 ZCKJD31H7 ZCKJ2 ZCKJ7H29 ZCKJD37H7 ZCKJ9H7 ZCKJ9H7 ZCKJ1H7 ZCKJ11 ZCKJ035H7 ZCKJ11 ZCKJ039H7 ZCKJ11 ZCKJ11 ZCKJ039H7 ZCKJ11 ZCKJ039H7 ZCKJ11 ZCKJ039H7 ZCKJ11H29 ZCKJ11H29 ZCKJ11H29 ZCKJ11H29 ZCKJ2H29 ZCKJ11H7 ZCKJD37H29 ZCKJ2H29 ZCKJ11H29 ZCKJ2H29 ZCKJ11H29 ZCKJ8H29 ZCKJ8H29 ZCKJ8H29 ZCKJ8H29 ZCKJ2H29 ZCKJ8H29 ZCKJ8H29 ZCKJ8H29 ZCKJ8H29 ZCKJ8H29 ZCKJ8H29 ZCKJ8H7 ZCKJB37 ZCKJB47 ZCKJB37 ZCKJB47 ZCKJB39 ZCKJB49 ZCKJB47 ZCKJB7 ZCKJB7 ZCKJB1 ZCKJB1 ZCKJB1 ZCKJ1H2 ZCKJ1	Series name	Standard format
Head type Multi-directional head Product compatibility XCKJ Associated body ZCKJ/H7	· .	Limit switch head
Product compatibility XCKJ Associated body ZCKJ7H7	Device short name	ZCKE
Associated body ZCKJ7H7	Head type	Multi-directional head
ZCKJD31H7 ZCKJ2 ZCKJTH29 ZCKJD37H7 ZCKJ9H7 ZCKJ9H7 ZCKJ9H7 ZCKJD35 ZCKJD35H7 ZCKJD35H7 ZCKJD39H7 ZCKJD39H7 ZCKJ6H29 ZCKJ9H29 ZCKJ9H29 ZCKJ9H29 ZCKJ11H29 ZCKJ2H29 ZCKJ11H7 ZCKJ5H7 ZCKJB37H29 ZCKJ11H29 ZCKJB37H29 ZCKJD37H29 ZCKJD37H29 ZCKJD37H29 ZCKJB37H29 ZCKJB37 ZCKJB37 ZCKJB37 ZCKJB37 ZCKJB37 ZCKJB37 ZCKJB37 ZCKJB37 ZCKJB37 ZCKJB39 ZCKJ21H7 ZCKJB47 ZCKJ	Product compatibility	XCKJ
head Type of operator Spring rod spring return	Associated body	ZCKJD31H7 ZCKJ2 ZCKJ7H29 ZCKJD37H7 ZCKJ9H7 ZCKJ9H7 ZCKJD35 ZCKJD35H7 ZCKJD35H7 ZCKJD39H7 ZCKJ6H29 ZCKJ6H29 ZCKJ6H29 ZCKJ11H7 ZCKJ5H7 ZCKJ5H7 ZCKJSH7 ZCKJSH7 ZCKJD37H29 ZCKJ11H7 ZCKJD37H29 ZCKJD31H29 ZCKJBH29 ZCKJ2H29 ZCKJ2H29 ZCKJ2H29 ZCKJSH7 ZCKJB3H29 ZCKJ2H147 ZCKJB37 ZCKJB47
Type of approach Multi-directional approach	Type of operator	Spring rod spring return
	Type of approach	Multi-directional approach

Complementary

o op. o o		
Switch actuation	By any moving part	
Positive opening	Without	
Net weight	0.125 kg	
Head material	Metal	

Environment

Ambient air temperature for operation	10120 °C
Ambient air temperature for storage	10120 °C
Environmental characteristic	High temperature

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.8 cm
Package 1 Width	16.7 cm
Package 1 Length	3.9 cm
Package 1 Weight	136.0 g
Unit Type of Package 2	S01
Number of Units in Package 2	18
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.611 kg
Package 2 vveignt	2.611 Kg

Offer Sustainability

Sustainable offer status	Green Premium product
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------