



Parametry podstawowe

Gama produktów	Telemecanique Photoelectric sensors XU
Kategoria akcesoriów / części oddzielnych	Akcesoria do czujnika
Typ akcesoriów / części oddzielnych	Odbłyśnik
Przeznaczenie akcesoriów / części oddzielnych	Standardowy czujnik fotoelektryczny odbiciowy
Kształt odbłyśnika	Okrągły
Sprzedaż zgodnie z niepodzielną liczbą	1

Parametry uzupełniające

Wymiary akcesoriów	Ø 31 mm
Masa produktu	0,005 kg

Jednostka opakowania

Jednostka miary opakowania 1	PCE
Ilość jednostek w opakowaniu 1	1
Wysokość opakowania 1	1,900 cm
Szerokość opakowania 1	5,300 cm
Długość opakowania 1	10,700 cm
Waga opakowania 1	6,000 g
Jednostka miary opakowania 2	S01
Ilość jednostek w opakowaniu 2	100
Wysokość opakowania 2	15 cm
Szerokość opakowania 2	15 cm
Długość opakowania 2	40 cm
Waga opakowania 2	868,000 g

Oferta zrównoważonego rozwoju

Stan trwałej oferty	Produkt Green Premium
Ustawa Proposition 65 (Kalifornia)	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
W przypadku wszystkich zapytań Reach Rohs skontaktuj się z nami pod adresem	sustainability@tesensors.com

Warunki gwarancji

Gwarancja	18 months
-----------	-----------

Karta danych technicznych XUZC31

produktu

Dimensions Drawings

Dimensions

