

WLS15XDW0360DSQP

▶ WLS15 LOW PROFILE, LOW POWER LED STRIP LIGHT



WLS15 Work Light Strip; Diffused Window; Length:
360 mm

Voltage: 12 or 24 V dc; Environmental Rating:
IP66,67

Color: Daylight White

150 mm (6 in) 4-pin M12 PVC Pigtail QD


Part Number: 802032

CERTIFICATIONS



ACCESSORIES TO COMPLETE YOUR SYSTEM

Add all or individual items to your cart. More options available below.

| | |
|--|---|
|  | <p>LC15T-127AP2RBGQP</p> <p>LC15T Light Controller; 3-Color Touch Sensor Voltage: 10-30 V dc; 4 A; Environmental Rating: IP66, IP67 Colors: Red Blue Green; 2-Wire PWM Control 150 mm (6 in) 4-pin M12 Male-Female PVC Pigtail QDs</p> |
|--|---|






SPECIFICATIONS

| | |
|---|---|
| Power | DC |
| Cable Length (m) | 0.15 |
| IP Rating | IP66, IP67 |
| Display | No |
| Housing Style | Linear Strip |
| Primary Housing Material | Polycarbonate |
| Illumination | Yes |
| Mounting Thread | No Thread |
| Color Input Control | Individual (One wire/color, same number of colors as input wires) |
| Number of Colors | 1 |
| Product Size (mm) | 15 |
| Color Technology | Standard LED |
| Color Option 1 | Daylight White |
| Connection | Pigtail QD |
| Quick Disconnect Type | M12 |
| Lumens Color 1 | 350 |
| Color 1 - Wavelength/Color Temp/Coordinates | 5000K (Daylight) |
| Max Current Color (mA) | 480 |
| Dimming Option | PWM |

| | |
|---------------------------------------|------------------------|
| Number of Input Pins/Conductors | 4 |
| Supply Voltage | 12/24 V dc |
| Illuminated Length (LxWxH mm) | 286.4 |
| Physical Dimensions (LxWxH or DxH mm) | 360.0 x 30.6 x 15.5 |
| Environmental Rating | IP66; IP67 |
| High Temperature (up to 100° C) | 60 |
| Min Op. Temperature (°C) | -40 |
| Storage Temp (°C) | -40 to 70 |
| Primary Window Material | Polycarbonate Diffused |
| Secondary Material | Polyamide |
| Feature: Audible | No |
| Feature: Quick Disconnect | Yes |

COMPATIBLE PRODUCTS

BRACKETS









| | |
|---|--|
|  | <p>LMBWLS15</p> <p>Bracket: For Use with WLS15 Mounting Clip Kit Contains 3 Brackets</p> |
|  | <p>LMBWLS15-150S</p> <p>Bracket: For Use with WLS15 150 Degree Rotation Set of Two Stainless Steel</p> |
|  | <p>LMBWLS15MAG</p> <p>Bracket: For Use with WLS15 Magnetic Mounting Kit Set of Two Up to 16 lb Pull</p> |
|  | <p>LMBWLS15TD</p> <p>Two strips of 3M Dual Lock adhesive</p> |
|  | <p>LMBWLS15TF</p> <p>Two strips of double sided foam urethane tape</p> |

DOUBLE-ENDED CORDSETS

| | |
|---|--|
|  | <p>MQDEC-401SS</p> <p>Double-Ended M12 Cable 300 mm 4-pin Straight Female; 4-pin Straight Male 0.31 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p> |
|  | <p>MQDEC-403SS</p> <p>Double-Ended M12 Cable 1 m 4-pin Straight Female; 4-pin Straight Male 0.91 m Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p> |
|  | <p>MQDEC-406SS</p> <p>Double-Ended M12 Cable 1.8 m 4-pin Straight Female; 4-pin Straight Male 1.83 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p> |

| | |
|---|--|
|  | <p>MQDEC-412SS</p> <p>Cordset Double Ended M12 to M12 4-pin Straight Female; 4-pin Straight Male 3.66 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p> |
|  | <p>MQDEC-420SS</p> <p>Cordset Double Ended M12 to M12 4-pin Straight Female; 4-pin Straight Male 6.1 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p> |
|  | <p>MQDEC-430SS</p> <p>Cordset Double Ended M12 to M12 4-pin Straight Female; 4-pin Straight Male 9.2 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p> |
|  | <p>MQDEC-450SS</p> <p>Cordset Double Ended M12 to M12 4-pin Straight Female; 4-pin Straight Male 15.2 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p> |

SINGLE-ENDED CORDSETS

| | |
|---|---|
|  | <p>MQDC-406</p> <p>Cordset Single Ended A-Code M12 4-pin Straight Female Connector 2 m (6.56 ft) Black PVC Jacket Nickel-Plated Brass Coupling Nut</p> |
|  | <p>MQDC-406RA</p> <p>Cordset Single Ended M12 4-pin Right-Angle Female 2 m (6.56 ft) 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p> |
|  | <p>MQDC-415</p> <p>Cordset Single Ended M12 4-pin Straight Female 5 m (16.4 ft) 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p> |
|  | <p>MQDC-415RA</p> <p>Cordset Single Ended M12 4-pin Right-Angle Female 5 m (16.4 ft) 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p> |
|  | <p>MQDC-430</p> <p>Cordset Single Ended M12 4-pin Straight Female 9 m (29.53 ft) 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p> |
|  | <p>MQDC-430RA</p> <p>Cordset Single Ended M12 4-pin Right-Angle Female 9 m (29.53 ft) 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p> |
|  | <p>MQDC-450</p> <p>Cordset Single Ended M12 4-pin Straight Female 15 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p> |
|  | <p>MQDC-450RA</p> <p>Cordset Single Ended M12 4-pin Right-Angle Female 15 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p> |

MECHANICAL SWITCHES



LC65P2T

LED Dimmer Module; 2 -Wire
Pulse Width Modulation
12-30 V dc; 4 A
Terminal Connection

OUTLET PLUG POWER SUPPLIES



PSD-24-4

DC Power Supply - Desktop Style
Input: 90-264 V ac 50/60 Hz; 1.8 m (6 ft) US Style Outlet Plug
Output: 24 V dc 4 A; 2 m (6.5 ft) 4-pin M12 QD
UL Listed Class 2



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America