

WLS15XDW0640DSQP

▶ WLS15 LOW PROFILE, LOW POWER LED STRIP LIGHT



WLS15 Work Light Strip; Diffused Window; Length: 640 mm

Voltage: 12 or 24 V dc; Environmental Rating: IP66,67

Color: Daylight White

150 mm (6 in) 4-pin M12 PVC Pigtail QD

Part Number: 802034

CERTIFICATIONS



ACCESSORIES TO COMPLETE YOUR SYSTEM

Add all or individual items to your cart. More options available below.

	<p>LC15T-127AP2RBGQP</p> <p>LC15T Light Controller; 3-Color Touch Sensor Voltage: 10-30 V dc; 4 A; Environmental Rating: IP66, IP67 Colors: Red Blue Green; 2-Wire PWM Control 150 mm (6 in) 4-pin M12 Male-Female PVC Pigtail QDs</p>
--	---






SPECIFICATIONS

Power	DC
Cable Length (m)	0.15
IP Rating	IP66, IP67
Display	No
Housing Style	Linear Strip
Primary Housing Material	Polycarbonate
Illumination	Yes
Mounting Thread	No Thread
Color Input Control	Individual (One wire/color, same number of colors as input wires)
Number of Colors	1
Product Size (mm)	15
Color Technology	Standard LED
Color Option 1	Daylight White
Connection	Pigtail QD
Quick Disconnect Type	M12
Lumens Color 1	700
Color 1 - Wavelength/Color Temp/Coordinates	5000K (Daylight)
Max Current Color (mA)	960
Dimming Option	PWM

Number of Input Pins/Conductors	4
Supply Voltage	12/24 V dc
Illuminated Length (LxWxH mm)	566.4
Physical Dimensions (LxWxH or DxH mm)	640.0 x 30.6 x 15.5
Environmental Rating	IP66; IP67
High Temperature (up to 100° C)	60
Min Op. Temperature (°C)	-40
Storage Temp (°C)	-40 to 70
Primary Window Material	Polycarbonate Diffused
Secondary Material	Polyamide
Feature: Audible	No
Feature: Quick Disconnect	Yes

COMPATIBLE PRODUCTS

BRACKETS









	<p>LMBWLS15</p> <p>Bracket: For Use with WLS15 Mounting Clip Kit Contains 3 Brackets</p>
	<p>LMBWLS15-150S</p> <p>Bracket: For Use with WLS15 150 Degree Rotation Set of Two Stainless Steel</p>
	<p>LMBWLS15MAG</p> <p>Bracket: For Use with WLS15 Magnetic Mounting Kit Set of Two Up to 16 lb Pull</p>
	<p>LMBWLS15TD</p> <p>Two strips of 3M Dual Lock adhesive</p>
	<p>LMBWLS15TF</p> <p>Two strips of double sided foam urethane tape</p>

DOUBLE-ENDED CORDSETS

	<p>MQDEC-401SS</p> <p>Double-Ended M12 Cable 300 mm 4-pin Straight Female; 4-pin Straight Male 0.31 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p>
	<p>MQDEC-403SS</p> <p>Double-Ended M12 Cable 1 m 4-pin Straight Female; 4-pin Straight Male 0.91 m Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p>
	<p>MQDEC-406SS</p> <p>Double-Ended M12 Cable 1.8 m 4-pin Straight Female; 4-pin Straight Male 1.83 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p>

	<p>MQDEC-412SS</p> <p>Cordset Double Ended M12 to M12 4-pin Straight Female; 4-pin Straight Male 3.66 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p>
	<p>MQDEC-420SS</p> <p>Cordset Double Ended M12 to M12 4-pin Straight Female; 4-pin Straight Male 6.1 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p>
	<p>MQDEC-430SS</p> <p>Cordset Double Ended M12 to M12 4-pin Straight Female; 4-pin Straight Male 9.2 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p>
	<p>MQDEC-450SS</p> <p>Cordset Double Ended M12 to M12 4-pin Straight Female; 4-pin Straight Male 15.2 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nuts</p>

SINGLE-ENDED CORDSETS

	<p>MQDC-406</p> <p>Cordset Single Ended A-Code M12 4-pin Straight Female Connector 2 m (6.56 ft) Black PVC Jacket Nickel-Plated Brass Coupling Nut</p>
	<p>MQDC-406RA</p> <p>Cordset Single Ended M12 4-pin Right-Angle Female 2 m (6.56 ft) 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p>
	<p>MQDC-415</p> <p>Cordset Single Ended M12 4-pin Straight Female 5 m (16.4 ft) 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p>
	<p>MQDC-415RA</p> <p>Cordset Single Ended M12 4-pin Right-Angle Female 5 m (16.4 ft) 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p>
	<p>MQDC-430</p> <p>Cordset Single Ended M12 4-pin Straight Female 9 m (29.53 ft) 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p>
	<p>MQDC-430RA</p> <p>Cordset Single Ended M12 4-pin Right-Angle Female 9 m (29.53 ft) 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p>
	<p>MQDC-450</p> <p>Cordset Single Ended M12 4-pin Straight Female 15 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p>
	<p>MQDC-450RA</p> <p>Cordset Single Ended M12 4-pin Right-Angle Female 15 m 4x22 Black PVC Jacket Nickel-Plated Brass Coupling Nut</p>

MECHANICAL SWITCHES



LC65P2T

LED Dimmer Module; 2 -Wire
Pulse Width Modulation
12-30 V dc; 4 A
Terminal Connection

OUTLET PLUG POWER SUPPLIES



PSD-24-4

DC Power Supply - Desktop Style
Input: 90-264 V ac 50/60 Hz; 1.8 m (6 ft) US Style Outlet Plug
Output: 24 V dc 4 A; 2 m (6.5 ft) 4-pin M12 QD
UL Listed Class 2



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America