

PRODUCT-DETAILS

LS32M41B11

LS32M41B11 Limit Switch



General Information

| | |
|-----------------------|---|
| Extended Product Type | LS32M41B11 |
| Product ID | 1SBV011941R1211 |
| EAN | 3471522621436 |
| Catalog Description | LS32M41B11 Limit Switch |
| Long Description | LS32M41B11 is a 30 mm wide, standard Limit Switch made of zinc alloy material (Zamak), with 2 mounting holes at the top, 1 ISO M16x1.5 cable entry on the bottom, plastic roller lever (Ø18 mm) actuator and 1 N.O + 1 N.C snap action (Zb type) contacts |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC141160C0201 |
| Instructions and Manuals | 1SBC141160C0201 |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 30 mm |
| Product Net Height | 108 mm |

| | |
|----------------------------|----------|
| Product Net Depth / Length | 44 mm |
| Product Net Weight | 0.178 kg |

Technical

| | |
|--|---|
| Action Type of the Contact Element (acc. to IEC 60947-5-1) | Snap Action Simultaneous |
| Actuator Type | plastic roller lever (Ø18 mm) |
| B10d Value | 30 Millions operations |
| Conventional Free-air Thermal Current (I _{th}) | acc. to IEC 60947-5-1, q = 40 °C 10 A |
| Degree of Protection | acc. to IEC 60529 IP66 |
| Housing Material | Metal |
| Maximum Electrical Switching Frequency | (AC-15) 3600 cycles per hour (DC-13) 3600 cycles per hour |
| Maximum Mounted Auxiliary Contacts | 1 NO, 1 NC |
| Mechanical Durability | 0 cycle |
| Mounting Type | 30 mm (EN 50047) |
| Number and Type of Bottom Cable Glands | 1 x M16x1.5 - Bottom |
| Pilot Duty of Contact Elements acc. UL508 | A600 Q600 |
| Rated Impulse Withstand Voltage (U _{imp}) | 6 kV |
| Rated Operational Current AC-15 (I _e) | (230 V AC) 3.1 A (400 V) NC 4 (24 V) 10 A (130 V) 5.5 A (240 V) 3 A |
| Rated Insulation Voltage (U _i) | acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 500 V acc. to UL/CSA 600 V |
| Rated Operational Current DC-13 (I _e) | (24 V) 6 A (110 V) 0.6 A (125 V) 0.55 A (250 V) 0.4 A |
| Short-Circuit Protective Devices | gG Type Fuses 10 A |

Environmental

| | |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 ... +70 °C Storage -30 ... +80 °C |
| RoHS Status | Following EU Directive 2011/65/EU |

Certificates and Declarations (Document Number)

| | |
|----------------------------------|---------------------|
| CQC Certificate | CQC2004010305127663 |
| cUL Certificate | 9AKK107991A7379 |
| Declaration of Conformity - CCC | 2020980305001785 |
| Declaration of Conformity - CE | 1SBD250883U1000 |
| Declaration of Conformity - UKCA | 1SBD250886U1000 |
| Instructions and Manuals | 1SBC141160C0201 |
| RoHS Information | 1SBD250883U1000 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 54 mm |
| Package Level 1 Depth / Length | 32 mm |
| Package Level 1 Height | 118 mm |
| Package Level 1 Gross Weight | 0.192 kg |
| Package Level 1 EAN | 3471522621436 |

Classifications

| | |
|----------------------------|------------------------------------|
| Object Classification Code | B |
| ETIM 4 | EC001829 - Position switch modular |
| ETIM 5 | EC001829 - Position switch modular |
| ETIM 6 | EC000030 - End switch |
| ETIM 7 | EC000030 - End switch |
| eClass | V11.0 : 27272601 |
| UNSPSC | 39121500 |

Categories

Low Voltage Products and Systems → Control Products → Sensors → Limit Switches

