



 PRODUCT-DETAILS

YO XT5-XT6 24...60 Vac/dc

YO XT5-XT6 24...60 Vac/dc



General Information

| | |
|-----------------------|--|
| Extended Product Type | YO XT5-XT6 24...60 Vac/dc |
| Product ID | 1SDA104925R1 |
| EAN | 8015644070175 |
| Catalog Description | YO XT5-XT6 24...60 Vac/dc |
| Long Description | SHUNT OPENING RELEASE FOR PERMANENT SERVICE 24...60V AC-DC XT5-XT6 |

Environmental

| | |
|---------------------------|-----------------|
| Environmental Information | 9AKK108467A6707 |
|---------------------------|-----------------|

Material Compliance

| | |
|-------------------|--|
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Conflict Minerals | 9AKK108467A5658 |

Reporting Template
(CMRT)

Toxic Substances Control Act - TSCA 9AKK108467A8326

Ordering

| | |
|--------------------------|---------------|
| Order Code US and Canada | KXTFYOB |
| E-Number (Finland) | 3642163 |
| EAN | 8015644070175 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85389099 |

Dimensions

| | |
|--------------------|---------|
| Product Net Weight | 0.12 kg |
|--------------------|---------|

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 110 mm |
| Package Level 1 Height | 60 mm |
| Package Level 1 Depth / Length | 140 mm |
| Package Level 1 Gross Weight | 0.15 kg |
| Package Level 1 EAN | 8015644070175 |

Additional Information

| | |
|----------------------------|-------------------------|
| Product Main Type | Accessories for Tmax XT |
| Product Name | Accessory |
| Product Type | Accessory |
| Suitable For | XT5 XT6 |
| Suitable for Product Class | SACE Tamx XT |

Technical

| | |
|---------------------------------|------------------------------|
| Configuration Type | Loose or configurable |
| Current Type | AC/DC |
| Order Multiple | 1 piece |
| Rated Voltage (U _r) | 24...60 V AC 24...60 V DC |
| Standards | IEC60947-2 UL489 |

Certificates and Declarations

| | |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0206 1SDC210200D0206 |
|-----------------------------------|------------------------------------|

Declaration of
Conformity - CE

Refer to the EU Declaration of the relative Circuit Breaker

Instructions and
Manuals

1SDH002011A1511

Classifications

| | |
|------------------------------------|--|
| ETIM 8 | EC002483 - Switch spool for power circuit breaker |
| ETIM 9 | EC002483 - Switch spool for power circuit breaker |
| IDEA Granular Category Code (IGCC) | 4879 >> Shunt release (for power circuit breaker) |
| UNSPSC | 39121601 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | V11.1 : 27370421 |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Accessories for Tmax XT

