

## Han 3A Hood Top Entry M25 Low Constr.



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 20 003 1421                                                                        |
| Specification      | Han 3A Hood Top Entry M25 Low Constr.                                                 |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19200031421">https://b2b.harting.com/19200031421</a> |

### Identification

|                             |                             |
|-----------------------------|-----------------------------|
| Category                    | Hoods/Housings              |
| Series of hoods/housings    | Han A <sup>®</sup>          |
| Type of hood/housing        | Hood                        |
| Description of hood/housing | With integrated cable gland |

### Version

|                      |                                                     |
|----------------------|-----------------------------------------------------|
| Locking type         | Single locking lever                                |
| Size                 | 3 A                                                 |
| Version              | Top entry                                           |
| Cable entry          | 1x Integrated                                       |
| Field of application | Standard Hoods/housings for industrial applications |

### Technical characteristics

|                                        |                                                    |
|----------------------------------------|----------------------------------------------------|
| Limiting temperature                   | -40 ... +125 °C                                    |
| Degree of protection acc. to IEC 60529 | IP44<br>IP65 / IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E     | 12                                                 |
| Cable diameter                         | 6 ... 12 mm                                        |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Zinc die-cast        |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 7037 (dust grey) |



Pushing Performance

## Material properties

|                             |                                                        |
|-----------------------------|--------------------------------------------------------|
| RoHS                        | compliant with exemption                               |
| RoHS exemptions             | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                  | compliant with exemption                               |
| China RoHS                  | 50                                                     |
| REACH Annex XVII substances | No                                                     |
| REACH ANNEX XIV substances  | No                                                     |
| REACH SVHC substances       | Yes                                                    |
| REACH SVHC substances       | Lead                                                   |

## Specifications and approvals

|           |                                                            |
|-----------|------------------------------------------------------------|
| Approvals | DNV GL                                                     |
| UL / CSA  | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE        | Yes                                                        |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 10                                       |
| Net weight                     | 78.58 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |