

## Han 32A-gs-QB-M25



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 20 032 1531                                                                        |
| Specification      | Han 32A-gs-QB-M25                                                                     |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19200321531">https://b2b.harting.com/19200321531</a> |

### Identification

|                          |                    |
|--------------------------|--------------------|
| Category                 | Hoods/Housings     |
| Series of hoods/housings | Han A <sup>®</sup> |
| Type of hood/housing     | Hood               |
| Type                     | Low construction   |

### Version

|                            |                                                     |
|----------------------------|-----------------------------------------------------|
| Locking type               | Double locking lever (on the hood)                  |
| Han-Easy Lock <sup>®</sup> | Yes                                                 |
| Size                       | 32 A                                                |
| Version                    | Side entry                                          |
| Cable entry                | 1x M25                                              |
| Field of application       | Standard Hoods/housings for industrial applications |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65            |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12   |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast   |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 7037 (dust grey) |



Pushing Performance

## Material properties

|                                                            |                                                           |
|------------------------------------------------------------|-----------------------------------------------------------|
| Material (locking)                                         | Polycarbonate (PC)<br>Stainless steel                     |
| Colour (locking)                                           | RAL 7037 (dust grey)                                      |
| Material flammability class acc. to UL 94 (locking levers) | V-0                                                       |
| RoHS                                                       | compliant                                                 |
| ELV status                                                 | compliant                                                 |
| China RoHS                                                 | e                                                         |
| REACH Annex XVII substances                                | No                                                        |
| REACH ANNEX XIV substances                                 | No                                                        |
| REACH SVHC substances                                      | Yes                                                       |
| REACH SVHC substances                                      | Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
| CE        | Yes    |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 230 g                                    |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |