

PRODUCT-DETAILS

CA5-22M

CA5-22M Auxiliary Contact Block



General Information

Extended Product Type	CA5-22M
Product ID	1SBN010040R1122
EAN	3471522121141
Catalog Description	CA5-22M Auxiliary Contact Block
Long Description	CA5-22M Auxiliary Contact Block

Technical

Product Name	Auxiliary Contact Block
Suitable For	<ul style="list-style-type: none"> A9 A12 A16 A26 A30 A40 AL9 AL9Z AL12 AL12Z AL16 AL16Z AL26 AL30 AL40 TAL9 TAL12 TAL16 TAL26

TAL30
TAL40
UA16
UA26
UA30

Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Rated Frequency (f)	Supply Circuit 50 / 60 Hz
Minimum Switching Capacity	A9 ... A40-30-10 17 / 5 VLT4K
Power Loss	at Rated Operating Conditions per Pole 0.1 W
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A
Mechanical Durability	10 million
Number of Auxiliary Contacts NC	2
Number of Auxiliary Contacts NO	2
Mounting Type	Front mounting
Mounting Position	Front face
Remarks	100
Terminal Type	Screw Terminals

Environmental

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SBD250132E1001

Technical UL/CSA

Pilot Duty UL/CSA	A600 Q300
-------------------	--------------

Dimensions

Product Net Width	44 mm
Product Net Height	47 mm
Product Net Depth / Length	39 mm
Product Net Weight	0.06 kg

Container Information

Package Level 1 Units	2 piece
Package Level 1 Width	65 mm
Package Level 1 Height	43 mm
Package Level 1 Depth / Length	129.5 mm

Package Level 1 Gross Weight	0.12 kg
Package Level 1 EAN	3471522121141
Package Level 2 Units	box 200 piece
Package Level 2 Width	300 mm
Package Level 2 Height	308 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Gross Weight	12 kg
Package Level 3 Units	3600 piece

Ordering

Minimum Order Quantity	2 piece
Customs Tariff Number	85389099
E-Number (Finland)	3709191
Country of Origin	Czech Republic (CZ)
Selling Unit of Measure	piece

Certificates and Declarations (Document Number)

CB Certificate	CB_SE_62119A1
CCC Certificate	CCC_2015010304800518
CQC Certificate	CQC2015010304800518 CQC2004010305133985
CSA Certificate	CSA_1033838
Declaration of Conformity - CCC	2020980304001627 2020980305001185
Declaration of Conformity - CE	1SBD250809U1000
DNV GL Certificate	DNV_GL_TAE00001UT
EAC Certificate	EAC_RU C-FR ME77 B03391
Environmental Information	1SBD250132E1001
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	1SBC101012M5501
RINA Certificate	RINA_ELE172319XG001
RoHS Information	1SBD250809U1000
UL Certificate	UL_071301E48139

Popular Downloads

Data Sheet, Technical Information	1SBC100122C0202_Ch04
Instructions and Manuals	1SBC101012M5501

Classifications

ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8538 90 99

UNSPSC	39121500
eClass	V11.0 : 27371302
Object Classification Code	K

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

