



Product designation	Variable speed drives		
Product type designation	VLB3		
<b>General characteristics</b>			
Rated power supply voltage	Three phase 400...480VAC 50/60Hz		
Rated output voltage	VAC	Three-phase 0... 480VAC 0-599Hz	
Rated output current	A	5.6 (heavy load)	
Rated output power	kW	2.2 (Heavy load)	
EMC filter	Built-in EMC suppressor cat. C2		
Communication port	Built-in RS485, Modbus RTU protocol		
<b>Technical features</b>			
Input type	Three phase		
Rated mains voltage	VAC	400...480	
Operating mains voltage range	VAC	340...528	
Rated mains frequency	Hz	50/60	
Operating mains frequency range	Hz	45...65	
Rated mains current without mains choke	7.8		
Rated mains current with mains choke	5.3		
Output type	three-phase		
Output voltage range	VAC	0...480	
Output frequency range	Hz	0...599	
Current overload	%/s	150% for 60s; 200% for 3s	
Apparent output power	3.6 (heavy load)		
Power loss	4kHz: 66W (heavy load)		
Brake chopper	Yes		
Switching frequency	2...16kHz		
Max motor cable length	Shielded		
	Without EMC category	m	50m / 100m (40°C max, switching frequency 4kHz max)
	Category C1	m	3
	Category C2	m	20
	Category C3	m	35
	Unshielded		

Without EMC category      m      200


**Functions**

Motor control modes	V/f linear, quadratic torque, sensorless vector control, ECO mode, servo control with encoder feedback, multipoint V/f curve, V/f closed loop control with encoder feedback, torque setpoint, sensorless control for synchronous motors up to 22kW
Speed reference signals	External potentiometer 0...10kΩ Voltage signals: 0...10VDC or -10...+10VDC Current signals: 0/4...20mA Buttons on front keyboard Door-mount installation kit 15 preset speeds via digital inputs Motor potentiometer Fieldbus
3-wire control	Yes
S-shape curves	Yes
Slip compensation	Yes
Flying restart	Yes
Access to DC bus	Yes
DC braking	Yes
DC injection at start	Yes
PID control	Yes, with sleep and rinse function
Sequencer (programmable frequency/time cycles)	Yes
Preset speeds	Yes
Motorpotentiometer	Yes
Different parameter configuration sets	Yes
Parameters changeover function	Yes
Favorite parameters menu	Yes
Autotuning	No
Safe torque Off (STO) safety function	Optional
PTC probe input	Yes

Protections			Overcurrent Output short circuit and earth/ground leakage Overvoltage Undervoltage Phase loss Motor heat overload (i2t) Overspeed Speed reverse
Special funct.			Multi-pump PID control (1 main pump frequency regulated + 2 auxiliary pumps activated in direct mode in case of necessity)
<b>Input and Output</b>			
Number of digital input	n°		5
Digital input type			Selectable PNP or NPN logic
Number of digital output	n°		2
Digital output arrangement			1 relay output with changeover contact (C/O-SPDT) + 1 digital output
Output contacts ratings			Relay output: 3A 250VAC Digital output: 100mA max 30VDC
Number of analog input	n°		2
Analog input type			Configurable 0/2...10VDC, -10...+10VDC, 0...5VDC, 0/4...20mA
Number of analog output	n°		1
Analog output type			configurable as 0...10VDC, 0...5VDC, 2...10VDC, 0/4...20mA
<b>Ambient conditions</b>			
Temperature			
	Operating temperature		
		min	°C -10
		max	°C +55

			switching frequency 2 or 4kHz: 2.5%/°C over 45°C switching frequency 8 or 16kHz: 2.5%/°C over 40°C
	Current derating		
Storage temperature			
	min	°C	-25
	max	°C	+60
Relative humidity		%	5...95% (with no condensing)
Max altitude		m	4000m (over 1000m derate the rated current by 5%/1000m)
Maximum Pollution degree			2
Overvoltage category			III up to 2000m altitude (II above 2000m)
<b>Housing</b>			
Installation position			Vertical
IP degree of protection			IP20
Dimensions (W x H x D)		mm	60 x 278 x 130
Weight		Kg	1.38
<b>Dimensions</b>			





## Certifications and compliance

### Compliance

CSA 22.2 n°274  
EN 61800-5-1  
UL61800-5-1

### Certificates

CSA  
cULus  
EAC  
RCM