


PRODUCT-DETAILS

# OT63F6

## OT63F6 SWITCH-DISCONNECTOR



### General Information

|                       |                                                                                                                                                                                  |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | OT63F6                                                                                                                                                                           |
| Product ID            | 1SCA105379R1001                                                                                                                                                                  |
| EAN                   | 6417019393155                                                                                                                                                                    |
| Catalog Description   | OT63F6 SWITCH-DISCONNECTOR                                                                                                                                                       |
| Long Description      | 6-pole, front operated, base mounted, DIN-rail mountable switch-d disconnecter / non-fusible disconnect switch with protected clamp terminals, handle and shaft are not included |

### Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85365080     |
| Country of Origin      | Finland (FI) |

### Popular Downloads

|                                   |                                                     |
|-----------------------------------|-----------------------------------------------------|
| Data Sheet, Technical Information | 1SCC301020C0201                                     |
| Instructions and Manuals          | 1SCC301066M0206                                     |
| Mechanical Drawings               | 1SCC301458F0001<br>1SCC301457F0001<br>OT63-80F6.igs |

## Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 105 mm  |
| Product Net Height         | 91.5 mm |
| Product Net Depth / Length | 84.5 mm |
| Product Net Weight         | 0.6 kg  |

## Technical

|                                                    |                                                                                  |
|----------------------------------------------------|----------------------------------------------------------------------------------|
| Rated Operational Current AC-21A ( $I_e$ )         | (380 ... 415 V) 63 A<br>(500 V) 63 A<br>(690 V) 63 A                             |
| Rated Operational Current AC-22A ( $I_e$ )         | (380 ... 415 V) 63 A<br>(500 V) 63 A<br>(690 V) 63 A                             |
| Rated Operational Current AC-23A ( $I_e$ )         | (380 ... 415 V) 63 A<br>(500 V) 45 A<br>(690 V) 20 A                             |
| Rated Operational Power AC-23A ( $P_e$ )           | (220 ... 240 V) 11 kW<br>(400 ... 415 V) 22 kW<br>(500 V) 22 kW<br>(690 V) 15 kW |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | q = 40 °C 63 A                                                                   |
| Conventional Thermal Current ( $I_{the}$ )         | Fully Enclosed 63 A                                                              |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )      | 8 kV                                                                             |
| Rated Insulation Voltage ( $U_i$ )                 | acc. to IEC/EN 60664-1 750 V                                                     |
| Rated Operational Voltage                          | Main Circuit 750 V                                                               |
| Rated Short-Circuit Making Capacity ( $I_{cm}$ )   | (690 V) 1.4 kA                                                                   |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | for 1 s 1 kA                                                                     |
| Power Loss                                         | at Rated Operating Conditions per Pole 2.8 W                                     |
| Pollution Degree                                   | 3                                                                                |
| Handle Type                                        | Knob<br>Handle and shaft not included                                            |
| Switches Operating Mechanism                       | Mechanism on Top of the Switch                                                   |
| Distance Between Phases                            | Standard                                                                         |
| Position of Line Terminals                         | Top In - Bottom Out<br>Bottom In - Top Out                                       |
| Operating Mode                                     | Front operated                                                                   |
| Standards                                          | IEC 60947-3 / UL 508 / CSA C22.2 No. 14                                          |
| Special Functions                                  | No                                                                               |
| Mounting Type                                      | Base mounting                                                                    |
| Number of Poles                                    | 6                                                                                |
| Cable Cross-Section                                | Cu 1.5...35 mm <sup>2</sup>                                                      |
| Degree of Protection                               | Front IP20                                                                       |
| Terminal Type                                      | Screw Terminals                                                                  |
| Tightening Torque                                  | acc. IEC 60947-1 2 N·m                                                           |
| Mechanical Durability                              | 20000                                                                            |
| Lock Type                                          | No                                                                               |

## Technical UL/CSA

|                                  |                                                                                                                                                                                                                                                                                  |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maximum Operating Voltage UL/CSA | 600 V                                                                                                                                                                                                                                                                            |
| Horsepower Rating UL/CSA         | (110 ... 120 V AC) Single Phase 2 Hp<br>(240 V AC) Single Phase 7.5 Hp<br>(440 ... 480 V AC) Single Phase 15 Hp<br>(550 ... 600 V AC) Single Phase 15 Hp<br>(220 ... 240 V AC) Three Phase 15 Hp<br>(440 ... 480 V AC) Three Phase 30 Hp<br>(550 ... 600 V AC) Three Phase 30 Hp |
| Ampere Rating UL/CSA             | 60 A                                                                                                                                                                                                                                                                             |
| Tightening Torque UL/CSA         | 18 in-lb                                                                                                                                                                                                                                                                         |

## Environmental

|                           |                                   |
|---------------------------|-----------------------------------|
| RoHS Status               | Following EU Directive 2011/65/EU |
| Environmental Information | 1SCC301183D0201                   |

## Certificates and Declarations (Document Number)

|                                |                           |
|--------------------------------|---------------------------|
| Declaration of Conformity - CE | 1SCC301167D2704           |
| Environmental Information      | 1SCC301183D0201           |
| Instructions and Manuals       | 1SCC301066M0206           |
| RoHS Information               | 1SCC301183D0202           |
| UL Certificate                 | cULus certificate OT16-80 |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 111 mm        |
| Package Level 1 Depth / Length | 205 mm        |
| Package Level 1 Height         | 102 mm        |
| Package Level 1 Gross Weight   | 0.65 kg       |
| Package Level 1 EAN            | 6417019393155 |

## Classifications

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 5                     | EC000216 - Switch disconnecter                             |
| ETIM 6                     | EC000216 - Switch disconnecter                             |
| ETIM 7                     | EC000216 - Switch disconnecter                             |
| ETIM 8                     | EC000216 - Switch disconnecter                             |
| UNSPSC                     | 39122233                                                   |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Finland)         | 3601453                                                    |

---

## Categories

---

Low Voltage Products and Systems → Switches → Switch Disconnectors

