


PRODUCT-DETAILS

# OT2000E04P

## OT2000E04P SWITCH-DISCONNECTOR



### General Information

Extended Product Type	OT2000E04P
Product ID	1SCA108038R1001
EAN	6417019413594
Catalog Description	OT2000E04P SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, base mounted switch-diconnector with black IP65 handle and shaft, terminal bolt kit included

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301078M0205
Mechanical Drawings	1SCC301518F0001 1SCC301517F0001 OT2500E04.igs

## Dimensions

Product Net Width	598.5 mm
Product Net Height	376.5 mm
Product Net Depth / Length	145.5 mm
Product Net Weight	33.3 kg

## Technical

Rated Operational Current AC-21B ( $I_e$ )	(380 ... 415 V) 2000 A (500 V) 2000 A (690 V) 2000 A
Rated Operational Current AC-22B ( $I_e$ )	(380 ... 415 V) 2000 A (500 V) 2000 A (690 V) 2000 A
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 2000 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 176 kA
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 55 kA
Power Loss	at Rated Operating Conditions per Pole 55 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch 04 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Terminal Width	100 mm
Tightening Torque	acc. IEC 60947-1 50...75 N·m
Mechanical Durability	6000
Lock Type	Yes

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202

---

## Certificates and Declarations (Document Number)

---

Declaration of Conformity - CE	1SCC301176D2702
DNV GL Certificate	1SCC301184D0203
Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301078M0205
RoHS Information	1SCC301149D0203

---

## Container Information

---

Package Level 1 Units	box 1 piece
Package Level 1 Width	580 mm
Package Level 1 Depth / Length	780 mm
Package Level 1 Height	500 mm
Package Level 1 Gross Weight	35.2 kg
Package Level 1 EAN	6417019413594

---

## Classifications

---

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
E-Number (Finland)	3641582

---

## Categories

---

Low Voltage Products and Systems → Switches → Switch Disconnectors

