

## Ordering information

### Plastic enclosed switch-disconnectors

#### Enclosed switch disconnectors, 2 pole, IP54

Enclosure in robust PBT plastic with metric threaded cable entries. Light grey box with dark grey cover and operating handle. Delivery includes PE terminal and membrane glands (IP54). The cover is interlocked.



BW225DP



BW225WDP



BW240DP



BW240WDP

#### Cable entries from top and bottom

Rated current		Cable outlets/side	Dimensions			Type	Order number	Weight /unit kg
AC-22A 415V	AC-23A 415V		Height mm	Width mm	Depth mm			
Auxiliary contacts included: none • Auxiliary contacts max: 1NO+0NC								
25	16	2xM25 / 2xM25	130	111	60	BW225DP	2CMA142400R1000	0.3
25	16		130	111	60	BW225WDP	2CMA142401R1000	0.3
40	32	2xM32 / 2xM32+M16	168	138	68	BW240DP	2CMA142407R1000	0.4
40	32		168	138	68	BW240WDP	2CMA100851R1000	0.4

## Ordering information

### Plastic enclosed switch-disconnectors



BW316TPN

#### Enclosed switch disconnectors, 3 pole, IP54

Enclosure in robust PBT plastic with metric threaded cable entries. Delivery includes neutral and PE terminal and membrane glands (IP54). The cover is interlocked.

##### Cable entries from top and bottom

Rated current		Cable outlets/side	Dimensions			Type	Order number	Weight /unit
AC-22A	AC-23A		side	Width	Depth			
415V	415V		mm	mm	mm			kg

##### Light grey enclosure with dark grey operating handle

Auxiliary contacts included: none • Auxiliary contacts max: 1NO+0NC

16	16		130	111	60	BW316TPN	2CMA142447R1000	0.3
25	16	2xM25 / 2xM25	130	111	60	BW325TPN	2CMA142403R1000	0.3
25	16		130	111	60	BW325WTPN <sup>1)</sup>	2CMA142402R1000	0.3
40	32		168	138	68	BW340TPN	2CMA142408R1000	0.4
40	32	2xM32 / 2xM32+M16	168	138	68	BW340WTPN <sup>1)</sup>	2CMA100852R1000	0.3

<sup>1)</sup> Light grey cover for commercial/residential design



BW325WTPN



BW340TPN

#### Enclosed switch disconnectors, 3 pole, IP54

Enclosure in robust PBT plastic with metric threaded cable entries. Delivery includes PE+neutral terminal and membrane glands / sealing plugs (IP54). \_L\_ type includes signal lamp.

##### Cable entries from top and bottom

Rated current		Cable outlets/side	Dimensions			Type	Order number	Weight /unit
AC-22A	AC-23A		Height	Width	Depth			
415V	415V		mm	mm	mm			kg

##### Light grey enclosure with dark grey operating handle

Auxiliary contacts included: none • Auxiliary contacts max: 1NO+0NC

25	16		130	111	60	BW325KTPN	2CMA142443R1000	0.3
25	16	2xM25 / 2xM25	130	111	60	BW325LTPN	2CMA142404R1000	0.3



BW340WTPN



BW325KTPN



BW325LTPN

## Ordering information

### Plastic enclosed switch-disconnectors

#### Enclosed switch disconnectors, 4 pole, IP65

Enclosure in robust PBT plastic with metric threaded cable entries. Delivery includes PE and switchable neutral terminal and membrane glands. The cover is interlocked.



BW425TPSN



BW440TPSN

#### Cable entries from top and bottom

Rated current		Cable outlets/side	Dimensions			Type	Order number	Weight /unit
AC-22A	AC-23A		Height	Width	Depth			
415V	415V		mm	mm	mm			kg

#### Light grey enclosure with dark grey operating handle

Auxiliary contacts included: none • Auxiliary contacts max: 1NO+0NC

25	16	2xM25 / 2xM25	130	111	60	BW425TPSN	2CMA142405R1000	0.3
25	16		130	111	60	BW425WTPSN	2CMA100850R1000	0.3
40	32	2xM32 / 2xM32+M16	168	138	68	BW440TPSN	2CMA142409R1000	0.4
40	32		168	138	68	BW440WTPSN	2CMA100853R1000	0.3

#### Enclosed switch disconnectors, 6 pole, IP65

Enclosure in robust PBT plastic with non-threaded cable entries. Delivery includes PE+neutral terminal and membrane glands (IP54).



BW625TPN

#### Cable entries from top and bottom

Rated current		Cable outlets/side	Dimensions			Type	Order number	Weight /unit
AC-22A	AC-23A		Height	Width	Depth			
415V	415V		mm	mm	mm			kg

#### Light grey box with dark grey cover and operating handle

Auxiliary contacts included: none • Auxiliary contacts max: 1NO+0NC

25	16	2xø25.5+ø16.5/	130	190	130	BW625TPN	2CMA142406R1000	0.5
40	25	2xø25.5+ø16.5	130	190	130	BW640TPN	2CMA142410R1000	0.5