

# ZCKJ7

Limit switch body, Limit switches XC Standard, ZCKJ, fixed, w/o display, 2NC, slow break, Pg13



## Main

|                               |  |
|-------------------------------|--|
| Range of product              | Telemecanique Limit switches XC Standard   |
| Series name                   | Standard format  |
| Product or component type     | Limit switch body  |
| Device short name             | ZCKJ   |
| Body type                     | Fixed  |
| Product compatibility         | XCKJ   |
| Associated head               | ZCKE05<br>ZCKE64<br>ZCKE08<br>ZCKE65<br>ZCKE66<br>ZCKE06<br>ZCKE629<br>ZCKE61<br>ZCKE23<br>ZCKE63<br>ZCKE619<br>ZCKE21<br>ZCKE67<br>ZCKE62 |
| Body material                 | Metal  |
| Cable entry                   | 1 entry tapped for Pg 13.5 cable gland   |
| Number of poles               | 2  |
| Contacts type and composition | 2 NC   |
| Contact operation             | Slow-break, simultaneous   |
| Number of steps               | 1 1 position   |
| Contacts material             | Silver plated contacts   |

## Complementary

|  |   |
|--|---|
| Local display                                | Without   |
| Electrical connection                        | Screw-clamp terminals, clamping capacity: 1 x 0.5...2 x 2.5 mm <sup>2</sup>   |
| Positive opening                             | With  |
| Minimum actuation speed                      | 6 m/min   |
| [Ie] rated operational current               | 3 A at 240 V, AC-15, A300 conforming to IEC 60947-5-1 appendix A<br>0.27 A at 250 V, DC-13, Q300 conforming to IEC 60947-5-1 appendix A   |
| [Ithe] conventional enclosed thermal current | 10 A  |
| [Ui] rated insulation voltage                | 500 V (pollution degree 3) conforming to IEC 60947-1 for contact block<br>300 V conforming to CSA C22.2 No 14 for contact block<br>300 V conforming to UL 508 for contact block   |
| Maximum resistance across terminals          | 0.25 mOhm conforming to IEC 60255-7 category 3  |
| [Uimp] rated impulse withstand voltage       | 6 KV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1  |
| Short-circuit protection                     | 10 A cartridge fuse, type gG  |
| Electrical durability                        | 5000000 Cycles, DC-13 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 Cycles, DC-13 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width  | 40 mm   |
| Height                                       | 77 mm   |

|                               |                        |
|-------------------------------|------------------------|
| Depth                         | 44 mm                  |
| Net weight                    | 0.31 kg                |
| Terminals description ISO n°1 | (21-22)NC<br>(11-12)NC |

## Environment

|                                       |   |
|---------------------------------------|---|
| IP degree of protection               | IP66  |
| IK degree of protection               | IK07  |
| Ambient air temperature for operation | -25...70 °C for standard environment<br>10...120 °C for high temperature<br>-40...70 °C for low temperature |
| Ambient air temperature for storage   | -40...120 °C  |
| Environmental characteristic          | High temperature<br>Standard environment<br>Low temperature   |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 4.0 cm   |
| Package 1 Width              | 8.5 cm   |
| Package 1 Length             | 4.5 cm   |
| Package 1 Weight             | 284.0 g  |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 24       |
| Package 2 Height             | 15.0 cm  |
| Package 2 Width              | 30.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 7.334 kg |

## Offer Sustainability

|  |   |
|--|---|
| Sustainable offer status                   | Green Premium product   |
| Toxic heavy metal free                     | Yes   |
| Environmental Disclosure                   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile                        | No need of specific recycling operations  |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|