

ZCKE629

Limit switch head, Limit switches XC Standard, ZCKE, steel roller plunger with protective boot



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJD37 ZCKJ41 ZCKJ7 ZCKJ11H7 ZCKJ9H7 ZCKJD37H29 ZCKJD31H29 ZCKJ2 ZCKJD39 ZCKJ1 ZCKJ41H7 ZCKJ21H7 ZCKJD39H29 ZCKJ2H29 ZCKJ11 ZCKJD35 ZCKJ8H29 ZCKJ21 ZCKJ7H7 ZCKJD39H7 ZCKJ9H29 ZCKJ6H7 ZCKJ5H29 ZCKJ1H29 ZCKJ4H7 ZCKJ2H7 ZCKJD31H7 ZCKJ5 ZCKJ5H7 ZCKJ1H7 ZCKJ41H29 ZCKJ6H29 ZCKJ7H29 ZCKJD37H7 ZCKJ11H29 ZCKJD35H7 ZCKJ8H7 ZCKJ9 ZCKJ6 ZCKJD31 ZCKJ8 ZCKJ4 ZCKJ4H29 ZCKJD35H29 ZCKJ21H29
Movement of operating head	Linear
Type of operator	Roller plunger spring return metal (with protective boot)
Type of approach	Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.2 cm
Package 1 Width	8.7 cm
Package 1 Length	4.6 cm
Package 1 Weight	148.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	48
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	7.438 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------